#### VPDES PERMIT FACT SHEET

This document gives pertinent information concerning the reissuance of the VPDES permit listed below. This permit is being processed as a Minor, Municipal permit. The effluent limitations contained in this permit will maintain the Water Quality Standards (WQS) of 9 VAC 25-260. The proposed discharge will result from the operation of a sewage treatment plant (SIC Code: 4952 - Sewerage Systems). This permit action consists of reissuing the permit with revisions to the permit, as needed, due to changes in applicable laws, guidance, and available technical information.

1. Facility Name and Address:

Fork Union Military Academy STP

PO Box 278

Fork Union, VA 23055

Location: 765 Academy Road

2. Permit No. VA0024147; Expiration Date: June 30, 2012

3. Owner: Fork Union Military Academy

Contact Name: LTC Todd M. Giszack
Title: Assistant to the President

Telephone No: (434) 842-4321

4. Description of Treatment Works Treating Domestic Sewage:

Total Number of Outfalls – 1

The facility serves a military academy with dormitories, staff housing, and dining hall as well as a motor lodge with a restaurant. All of these facilities are owned by the academy. The treatment units comprising the STP are shown in the schematics included in the permit reissuance application.

Average Discharge Flow (January 2012 – February 2011) = 0.024 MGD Design Average Flow = 0.099 MGD

5. Application Complete Date: January 1, 2012

Permit Writer: Kate B. Harrigan Date: April 30, 2012 Reviewed By: Dawn Jeffries Date: May 2, 2012

Public Comment Period: May 24, 2012 to June 23, 2012

6. Receiving Stream Name: North Creek

River Mile: Outfall 002: 3.52

Use Impairment: Yes Special Standards: None

Tidal Waters: No

Watershed Name: VAC – H20R James River/Bear Garden/South Creek

Basin: James (Middle); Subbasin: N/A

Section: 10; Class: III

7. Operator License Requirements per 9 VAC 25-31-200.C: Class III

8. Reliability Class per 9 VAC 25-790: Class II (assigned April 12, 1982)

9.	Permit Characterization:  ☑ Private □ Federal □ State □ POTW □ PVOTW □ Possible Interstate Effect □ Interim Limits in Other Document (attach copy of CSO)
10.	Discharge Location Description and Receiving Waters Information: Appendix A
11.	Antidegradation (AD) Review & Comments per 9 VAC 25-260-30: Tier Designation: North Creek: Tier 1
	The State Water Control Board's WQS include an AD policy. All state surface waters are provided one of three levels of AD protection. For Tier 1 or existing use protection, existing uses of the water body and the water quality to protect these uses must be maintained. Tier 2 waters have water quality that is better than the WQS. Significant lowering of the water quality of Tier 2 waters is not allowed without an evaluation of the economic and social impacts. Tier 3 waters are exceptional waters and are so designated by regulatory amendment. The AD policy prohibits new or expanded discharges into exceptional waters.
	The antidegradation review begins with a Tier determination. North Creek, in the vicinity of the discharge, is determined to be a Tier 1 water because North Creek is listed as impaired for aquatic life (benthics). Antidegradation baselines are not calculated for Tier 1 waters.
12.	Site Inspection: Performed by Noel Thomas on February 29, 2012
13.	Effluent Screening and Effluent Limitations: Appendix B
14.	Effluent toxicity testing requirements included per 9 VAC 25-31-220.D: ☐ Yes ☑ No
	<ul> <li>If "No," check one:</li> <li>✓ Municipal: This facility does not have a design flow ≥ 1.0 MGD, has no Significant Industrial Users (SIUs) or Categorical Industrial Users (CIUs), and is not deemed to have the potential to cause or contribute to instream toxicity.</li> <li>☐ Industrial: This facility's SIC Code(s) and activities contributing wastewater do not fall within the categories for which aquatic toxicity monitoring is required, the facility does not have an IWC = 33%, and the discharge is not deemed to have the potential to cause or contribute to instream toxicity.</li> </ul>
15.	Sewage sludge utilization and disposal options include the following: - transport of sewage sludge to the Old Dominion Landfill for disposal
16.	Bases for Special Conditions: Appendix C
17.	Material Storage per 9 VAC 25-31-280.B.2: This permit requires that the facility's O&M Manual include information to address the management of wastes, fluids, and pollutants which may be present at the facility to avoid unauthorized discharge of such materials.
18.	Antibacksliding Review per 9 VAC 25-31-220.L: This permit complies with Antibacksliding provisions of

The stream segment receiving the effluent is listed for aquatic life (benthics). A TMDL for this impairment has not been approved. The permit contains a re-opener condition that may allow the permit limits to be modified, in compliance with section 303(d)(4) of the Act once a TMDL is approved.

19. Impaired Use Status Evaluation per 9 VAC 25-31-220.D: The facility discharges directly to North Creek.

the VPDES Permit Regulation.


20. Regulation of Users per 9 VAC 25-31-280.B.9: There are no individual users contributing to the treatment works.

21.	Storm water Management per 9 vAC 25-51-120: Application Required? ☐ Yes ☑ No
	<ul> <li>If "No," check one:</li> <li>✓ STPs: This facility does not have a design flow ≥ 1.0 MGD, nor is it required to have an approved POTW pretreatment program under 9 VAC 25-31-10 et seq.</li> <li>☐ Others: This facility's SIC Code(s) and activities do not fall within the categories for which a Storm Water Application submittal is required.</li> </ul>
22.	Compliance Schedule per 9 VAC 25-31-250: In an email dated May 12, 2012, the permittee indicated they did not need a schedule of compliance for the more stringent copper limits or the new zinc limits which are now included at the 0.060 MGD flow tier.
23.	Variances/Alternative Limits or Conditions per 9 VAC 25-31-280.B, 100.J, 100.P, and 100.M: None
24.	Financial Assurance Applicability per 9 VAC 25: $N/A$ – This facility does not serve private residences that are not owned by the permittee.
25.	Virginia Environmental Excellence Program (VEEP) Evaluation per § 10.1-1187.1-7: At the time of this reissuance, is this facility considered by DEQ to be a participant in the Virginia Environmental Excellence Program in good standing at either the Exemplary Environmental Enterprise (E3) level or the Extraordinary Environmental Enterprise (E4) level? ☐ Yes ☑ No
26.	Nutrient Trading Regulation per 9 VAC 25-820: See Appendix B General Permit Required: ☐ Yes ☑ No
27.	Threatened and Endangered (T&E) Species Screening per 9 VAC 25-260-20 B.8: Because this is not an issuance or reissuance that allows increased discharge flows and because DGIF and DCR did not request to review the permit, T&E screening is not required.
28.	Public Notice Information per 9 VAC 25-31-280.B: All pertinent information is on file, and may be inspected and copied by contacting Kate Harrigan at: DEQ-Valley Regional Office, P.O. Box 3000, Harrisonburg, Virginia 22801, Telephone No. (540) 574-7850, kathleen.harrigan@deq.virginia.gov.
	Persons may comment in writing or by email to the DEQ on the proposed permit action, and may request a public hearing, during the comment period. Comments shall include the name, address, and telephone number of the writer, and shall contain a complete, concise statement of the factual basis for comments. Only those comments received within this period will be considered. The DEQ may decide to hold a public hearing if public response is significant. Requests for public hearings shall state the reason why a hearing is requested, the nature of the issues proposed to be raised in the public hearing and a brief explanation of how the requester's interests would be directly and adversely affected by the proposed permit action. Following the comment period, the Board will make a determination regarding the proposed permit action. This determination will become effective, unless the DEQ grants a public hearing. Due notice of any public hearing will be given.
29.	Historical Record: The original permit was issued September 1, 1975. The design flow was 0.075 MGD. On October 26, 1996, a liner that met the required coefficient of permeability of no more than 10 <sup>-6</sup> cm/second was installed. On December 14, 2000, the SWCB approved a Consent Special Order that required the facility be upgraded. On August 9, 2004, DEQ issued a CTO for the 0.099 MGD facility. On August 31, 2004, Outfall 001, located at RM 3.52 was taken out of service as flows were diverted to Outfall 002. Additional flow tiers of 0.060 MGD and 0.075 MGD were included at the 2007 reissuance.

#### APPENDIX A

## DISCHARGE LOCATION AND RECEIVING WATERS INFORMATION

Fork Union Military Academy STP discharges to North Creek in Fluvanna County. The topographical map below shows the location of the treatment facility and Outfall 002.




## **PLANNING INFORMATION**

Relevant points of interest within the watershed and in the vicinity of the discharge are shown on the Water Quality Assessment Review table and corresponding map below.

	·	WATER QUALIT	Y ASSESSMENTS	REVIEW			
		MIDDLE J	AMES RIVER BAS	IN			
			2/15/2012				
		IMPAI	RED SEGMENTS				
SEGMENT ID STREAM SEGMENT START SEGMENT END SEGMENT LENGTH PARAMETER							
H03R-04-PCB	James River	233.49	159.02	74.47	PCB in Fish Tissue		
H20R-02-BEN	North Creek	3.95	.70	3.25	Benthic		
H31R-02-BEN	Carys Creek	1.69	0.00	1.69	Benthic		
			PERMITS				
PERMIT	FACILITY	STREAM	RIVER MILE	LAT	LONG	WBID	
VA0024147	Fork Union Military Ac	North Creek	3.52	374527	781501	VAC-H20R	
VA0081639	Envoy at the Village	North Creek X-Trib	0.60	374528	781540	VAC-H20R	
VA0004138	Dominion - Bremo Power	James River	175.89	374230	781721	VAC-H20R	
VA0057606	Omohundro Well WTP	Martin Creek X Trib	0.39	374621	781739	VAV-H31R	
VA0071692	Carysbrook Holdings LLC	Rivanna River	9.95	374855	781337	VAV-H31R	
VA0089559	Morris Well WTP	Martins Creek X-Trib	0.47	374654	781621	VAV-H31R	
VA0091936	Kingsbridge STP	Able Creek UT	0.79	374853	781755	VAV-H31R	
		MONITO	ORING STATIONS				
STREAM	NAME	RIVER MILE	RECORD	LAT	LONG		
James River	2-JMS176.63	176.63	9/23/99	374416	0781809		
Rivanna River	2-RVN001.64	1.64	3/24/70	374550	0781106		
North Creek	2-NOR003.50	3.5	6/20/00	374550	0781106 F 0781501		
Unnamed Tributary		0.02	6/20/00	374528	0781021		
Able Creek	2-ABL001.40	1.4	7/2003	374810	0781021		
Rivanna River	2-RVN001.55	1.55	5/13/04	374546	0781105		
North Creek	2-NOR000.20	0.02	5/13/04 F 6/2/99	F 374443	▼ 0781223		
North Creek	2-NOR003.28	3.28	6/2/99	374527	0781458		
North Creek	2-NOR003.59	3.59	6/20/00	374525	▼ 0781502		
OWNER	STREAM	RIVER MILE	TER SUPPLY INTA	KES			
OWNER	SIKEAM	RIVER MILE					
	WA	TER QUALITY MANA	GEMENT PLANNI	NG REGULATION			
Is this discharge add	ressed in the WOMP regu						
	limitations or restrictions		tion impose on this d	lischarge?			
PARAMETER	ALLOCATION		·	_			
BOD5	14.07 kg/d						
		XX7.4 (E)	ERSHED NAME				
		VAV-H20R James Rive		k/South Creek			
		TATA TIZOTO DAINES TON	on Boar Garden Orce	WOOdiii Olook			

## Fork Union Military Academy - Water Quality Assessments Review February 15, 2012



#### FLOW FREQUENCY DETERMINATION

# MEMORANDUM DEPARTMENT OF ENVIRONMENTAL QUALITY VALLEY REGIONAL OFFICE

VALLET REGIONAL OFFICE

## 4411 Early Road – P.O. Box 3000

Harrisonburg, VA 22801

SUBJECT: Flow Frequency Determination

Fork Union Military Academy STP - VPDES Permit No. VA0024147, Fluvanna County

TO: Permit Processing File

FROM: Kate Harrigan DATE: May 7, 2012

This memo supersedes Brandon Kiracofe's flow frequency determination dated December 15, 2006.

Fork Union Military Academy STP discharges to North Creek at Fork Union, VA. Stream flow frequencies are required above the discharge point for use by the permit writer in developing effluent limitations for the VPDES permit reissuance.

The VDEQ conducted flow measurements on North Creek from 1990 to 2001. The measurements were made upstream of the Fork Union Military Academy STP outfall. The measurements were correlated with the same-day daily mean values from the continuous record gage on Fine Creek at Fine Creek Mills, VA (#02036500). The correlation was done by plotting the measurements and the daily mean values on a log/log graph, and performing a regression analysis. The measurements correlated well with the Fine Creek gage. A best-fit line (and equation) for the data set was established. The required flow frequencies for the measurement site were then calculated using the equation of the line and the flow frequencies for the entire period of record of the Fine Creek gage.

The critical flows at the Fork Union Military Academy STP Outfall 002 were determined by projecting the measurement site flows downstream. This analysis does not address any other discharges, withdrawals, or springs located upstream of Outfall 002.

The data for the reference gage, the measurement site, and Outfall 002 are presented below:

#### Fine Creek at Fine Creek Mills, VA (#02036500):

Drainage Area =  $22.1 \text{ mi}^2$ 

1030 -	0.09 cfs	High Flow 1010 =	2.5 cfc
_			
1Q10 =	$0.24  \mathrm{cfs}$	High Flow $7Q10 =$	3.1 cfs
7Q10 =	0.30 cfs	High Flow $30Q10 =$	5.8 cfs
30Q10 =	0.53 cfs	$\mathbf{H}\mathbf{M} =$	3.7 cfs
30Q5 =	0.98 cfs		

#### North Creek at Fork Union, VA (#02030760) measurement site:

Drainage Area =  $2.0 \text{ mi}^2$ 

1Q30 =	0.026 cfs	High Flow 1Q10 =	0.238 cfs
1Q10 =	0.050 cfs	High Flow $7Q10 =$	0.274 cfs
7Q10 =	0.058 cfs	High Flow $30Q10 =$	0.415 cfs
30Q10 =	0.085 cfs	HM =	0.308 cfs
30Q5 =	0.128 cfs		

#### North Creek at Outfall 002:

Drainage Area =  $2.013 \text{ mi}^2$ 

1Q30 =	0.0171 mgd	High Flow 1Q10 =	0.1510 mgd
1Q10 =	0.0322 mgd	High Flow 7Q10 =	0.1812 mgd
7Q10 =	0.0372 mgd	High Flow $30Q10 =$	0.2331 mgd
30Q10 =	0.0554 mgd	HM =	0.2013 mgd
30O5 =	0.0835 mgd		_

The high flow months are December through May.

## EFFLUENT/STREAM MIXING EVALUATION

Mixing zone predictions were made with the Virginia DEQ Mixing Zone Analysis Version 2.1 program. The predictions are based on the discharge and receiving stream characteristics, and are presented below.

0.060 MGD Annual Mix	0.060 MGD Wet Mix
Stream 7Q10 = 0.0372 MGD	Stream 7Q10 = 0.1812 MGD
Stream $30Q10 = 0.0554 \text{ MGD}$	Stream 30Q10 = 0.2331 MGD
Stream $1Q10 = 0.0322 \text{ MGD}$	Stream $1Q10 = 0.1510 \text{ MGD}$
Stream slope = $0.092329545$ ft/ft	Stream slope = $0.092329545$ ft/ft
Stream width $= 2.5 \text{ ft}$	Stream width $= 3.5 \text{ ft}$
Bottom scale = 5	Bottom scale = 5
Channel scale = 1	Channel scale = 1
Mixing Zone Predictions @ 7Q10	Mixing Zone Predictions @ 7Q10
Depth = .1063 ft	Depth = .1499 ft
Length $= 23.68 \text{ ft}$	Length $= 34.84 \text{ ft}$
Velocity = .566 ft/sec	Velocity = .7115 ft/sec
Residence Time = .0005 days	Residence Time = .0006 days
Recommendation: A complete mix assumption is appropriate for this	Recommendation: A complete mix assumption is appropriate for this
situation and the entire 7Q10 may be used.	situation and the entire 7Q10 may be used.
Mixing Zone Predictions @ 30Q10	Mixing Zone Predictions @ 30Q10
Depth = $.1183 \text{ ft}$	Depth = $.1692 \text{ ft}$
Length $= 21.54 \text{ ft}$	Length $= 31.28  \text{ft}$
Velocity = .6041 ft/sec	Velocity = .7661 ft/sec
Residence Time = .0004 days	Residence Time = .0005 days
Recommendation: A complete mix assumption is appropriate for this	Recommendation: A complete mix assumption is appropriate for this
situation and the entire 30Q10 may be used.	situation and the entire 30Q10 may be used.
Mixing Zone Predictions @ 1Q10	Mixing Zone Predictions @ 1Q10
Depth = $.1029 \text{ ft}$	Depth = $.1379 \text{ ft}$
Length = $24.38 \text{ ft}$	Length $= 37.54 \text{ ft}$
Velocity = .5548 ft/sec	Velocity = .6762 ft/sec
Residence Time = .0122 hours	Residence Time = .0154 hours
Recommendation: A complete mix assumption is appropriate for this	Recommendation: A complete mix assumption is appropriate for this
situation and the entire 1Q10 may be used.	situation and the entire 1Q10 may be used.
0.075 MGD Annual Mix	
U.U/3 MGD Allitual MIX	0.075 MGD Wet Mix
0.075 PROD Allitual IVIX	0.075 MGD Wet Mix
Stream 7Q10 = 0.0372 MGD	Stream 7Q10 = 0.1812 MGD
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD  Stream 30Q10 = 0.2331 MGD  Stream 1Q10 = 0.1510 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 3.5 ft  Bottom scale = 5  Channel scale = 1
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1162 ft  Length = 21.89 ft	Stream 7Q10 = 0.1812 MGD  Stream 30Q10 = 0.2331 MGD  Stream 1Q10 = 0.1510 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 3.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1556 ft  Length = 33.71 ft
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1	Stream 7Q10 = 0.1812 MGD  Stream 30Q10 = 0.2331 MGD  Stream 1Q10 = 0.1510 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 3.5 ft  Bottom scale = 5  Channel scale = 1
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1162 ft  Length = 21.89 ft	Stream 7Q10 = 0.1812 MGD  Stream 30Q10 = 0.2331 MGD  Stream 1Q10 = 0.1510 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 3.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1556 ft  Length = 33.71 ft
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1	Stream 7Q10 = 0.1812 MGD  Stream 30Q10 = 0.2331 MGD  Stream 1Q10 = 0.1510 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 3.5 ft  Bottom scale = 5  Channel scale = 1
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1162 ft  Length = 21.89 ft  Velocity = .5978 ft/sec  Residence Time = .0004 days  Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1162 ft  Length = 21.89 ft  Velocity = .5978 ft/sec  Residence Time = .0004 days  Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10  Depth = .1276 ft  Length = 20.14 ft  Velocity = .6328 ft/sec	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1  Mixing Zone Predictions @ 7Q10 Depth = .1162 ft Length = 21.89 ft Velocity = .5978 ft/sec Residence Time = .0004 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10 Depth = .1276 ft Length = 20.14 ft	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1162 ft  Length = 21.89 ft  Velocity = .5978 ft/sec  Residence Time = .0004 days  Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10  Depth = .1276 ft  Length = 20.14 ft  Velocity = .6328 ft/sec  Residence Time = .0004 days  Recommendation: A complete mix assumption is appropriate for this	Stream 7Q10 = 0.1812 MGD  Stream 30Q10 = 0.2331 MGD  Stream 1Q10 = 0.1510 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 3.5 ft  Bottom scale = 5  Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1  Mixing Zone Predictions @ 7Q10 Depth = .1162 ft Length = 21.89 ft Velocity = .5978 ft/sec Residence Time = .0004 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10 Depth = .1276 ft Length = 20.14 ft Velocity = .6328 ft/sec Residence Time = .0004 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.  Mixing Zone Predictions @ 1Q10 Depth = .113 ft Length = 22.44 ft	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD  Stream 30Q10 = 0.0554 MGD  Stream 1Q10 = 0.0322 MGD  Stream slope = 0.092329545 ft/ft  Stream width = 2.5 ft  Bottom scale = 5  Channel scale = 1  Mixing Zone Predictions @ 7Q10  Depth = .1162 ft  Length = 21.89 ft  Velocity = .5978 ft/sec  Residence Time = .0004 days  Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10  Depth = .1276 ft  Length = 20.14 ft  Velocity = .6328 ft/sec  Residence Time = .0004 days  Recommendation: A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.  Mixing Zone Predictions @ 30Q10  Depth = .113 ft	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1  Mixing Zone Predictions @ 7Q10 Depth = .1162 ft Length = 21.89 ft Velocity = .5978 ft/sec Residence Time = .0004 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10 Depth = .1276 ft Length = 20.14 ft Velocity = .6328 ft/sec Residence Time = .0004 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.  Mixing Zone Predictions @ 1Q10 Depth = .113 ft Length = 22.44 ft Velocity = .5874 ft/sec Residence Time = .0106 hours	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1  Mixing Zone Predictions @ 7Q10 Depth = .1556 ft Length = 33.71 ft Velocity = .7281 ft/sec Residence Time = .0005 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10 Depth = .1745 ft Length = 30.43 ft Velocity = .7806 ft/sec Residence Time = .0005 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.  Mixing Zone Predictions @ 1Q10 Depth = .144 ft Length = 36.11 ft
Stream 7Q10 = 0.0372 MGD Stream 30Q10 = 0.0554 MGD Stream 1Q10 = 0.0322 MGD Stream slope = 0.092329545 ft/ft Stream width = 2.5 ft Bottom scale = 5 Channel scale = 1  Mixing Zone Predictions @ 7Q10 Depth = .1162 ft Length = 21.89 ft Velocity = .5978 ft/sec Residence Time = .0004 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10 Depth = .1276 ft Length = 20.14 ft Velocity = .6328 ft/sec Residence Time = .0004 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.  Mixing Zone Predictions @ 1Q10 Depth = .113 ft Length = 22.44 ft Velocity = .5874 ft/sec	Stream 7Q10 = 0.1812 MGD Stream 30Q10 = 0.2331 MGD Stream 1Q10 = 0.1510 MGD Stream slope = 0.092329545 ft/ft Stream width = 3.5 ft Bottom scale = 5 Channel scale = 1  Mixing Zone Predictions @ 7Q10 Depth = .1556 ft Length = 33.71 ft Velocity = .7281 ft/sec Residence Time = .0005 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 7Q10 may be used.  Mixing Zone Predictions @ 30Q10 Depth = .1745 ft Length = 30.43 ft Velocity = .7806 ft/sec Residence Time = .0005 days Recommendation: A complete mix assumption is appropriate for this situation and the entire 30Q10 may be used.  Mixing Zone Predictions @ 1Q10 Depth = .144 ft Length = 36.11 ft Velocity = .6941 ft/sec

0.099 MGD Annual Mix	0.099 MGD Wet Mix
Stream 7Q10 = 0.0372 MGD	Stream 7Q10 = 0.1812 MGD
Stream 30Q10 = 0.0554 MGD	Stream 30Q10 = 0.2331 MGD
Stream 1010 = 0.0322 MGD	Stream 1010 = 0.1510 MGD
Stream slope = $0.092329545$ ft/ft	Stream slope = 0.092329545 ft/ft
Stream width $= 2.5 \text{ ft}$	Stream width $= 3.5 \text{ ft}$
Bottom scale = 5	Bottom scale = 5
Channel scale = 1	Channel scale = 1
Mixing Zone Predictions @ 7Q10	Mixing Zone Predictions @ 7Q10
Depth = $.131 \text{ ft}$	Depth = $.1645 \text{ ft}$
Length = 19.67 ft	Length $= 32.07 \text{ ft}$
Velocity = .6432 ft/sec	Velocity = .7531 ft/sec
Residence Time = .0004 days	Residence Time = .0005 days
Recommendation: A complete mix assumption is appropriate for this	Recommendation: A complete mix assumption is appropriate for this
situation and the entire 7Q10 may be used.	situation and the entire 7Q10 may be used.
Mixing Zone Predictions @ 30Q10	Mixing Zone Predictions @ 30Q10
Depth $= .1418 \text{ ft}$	Depth $= .1829 \text{ ft}$
Length $= 18.31 \text{ ft}$	Length $= 29.18 \text{ ft}$
Velocity = .6741 ft/sec	Velocity = .803 ft/sec
Residence Time = .0003 days	Residence Time = .0004 days
Recommendation: A complete mix assumption is appropriate for this	Recommendation: A complete mix assumption is appropriate for this
situation and the entire 30Q10 may be used.	situation and the entire 30Q10 may be used.
Mixing Zone Predictions @ 1Q10	Mixing Zone Predictions @ 1Q10
Depth $= .128 \text{ ft}$	Depth $= .1533 \text{ ft}$
Length $= 20.07 \text{ ft}$	Length $= 34.16 \text{ ft}$
Velocity = .6342 ft/sec	Velocity = .7213 ft/sec
Residence Time = .0088 hours	Residence Time = .0132 hours
Recommendation: A complete mix assumption is appropriate for this	Recommendation: A complete mix assumption is appropriate for this
situation and the entire 1Q10 may be used.	situation and the entire 1Q10 may be used.

#### APPENDIX B

#### EFFLUENT SCREENING AND EFFLUENT LIMITATIONS

#### **EFFLUENT LIMITATIONS**

A comparison of technology and water quality-based limits was performed and the most stringent limits were selected, as summarized in the table below.

Outfall 002 Final Limits Design Flow: 0.060 MGD

Outlan 002		Final Limits Design Flow. 0.000					· 0.000 MGD
	BASIS	Е	FFLUENT I	LIMITATIONS		MONITORING REQUIREMENTS	
PARAMETER	FOR LIMITS	Monthly Average		Maximum		Frequency	Sample Type
Flow (MGD)	1	N	L	NL		Continuous	TIRE
		Monthly	Average	Weekly Average			
CBOD <sub>5</sub> (Jun-Nov)	3,4,5	12 mg/L	2.7 kg/d	18 mg/L	4.1 kg/d	1/Week	4 HC
CBOD <sub>5</sub> (Dec-May)	2,3,4,5	25 mg/L	5.7 kg/d	40 mg/L	9.1 kg/d	1/Week	4 HC
Ammonia-N (Jun-Nov)(mg/L)	1,3	6.	.7	6.7		1/Month	4 HC
TSS	1	30 mg/L	6.8 kg/d	45 mg/L	10 kg/d	1/Month	4 HC
Effluent Chlorine (TRC)(mg/L)*	3	0.013		0.016		3/Day at 4-hr intervals	Grab
E. coli (N/100 mL) (geometric mean)	3	126		N	A	4/Month* or 2 /Week** 10 am to 4 pm	Grab
Copper, TR (µg/L)	3	1	8	18		1/Month	4 HC
Zinc, TR (µg/L)	3	16	50	160		1/Month	4.HC
		Mini	mum	Maxi	mum		
pH (S.U.)	2,3	6.0		9.0		1/Day	Grab
Dissolved Oxygen (mg/L)	3,4	7.6		NA		1/Day	Grab
Contact Chlorine (TRC)(mg/L)*	3,5	1.	.0	NA		3/Day at 4-hr intervals	Grab
Total Hardness (as CaCO <sub>3</sub> )(mg/L)	5	N	L	NA		1/Quarter	4 HC

 $NL = No\ Limitation,\ monitoring\ required$ 

TIRE = Totalizing, Indicating, and Recording equipment

NA = Not Applicable 4 HC = 4-Hour Composite

4/Month = 4 samples taken monthly, with at least 1 sample taken each calendar week

2/Week = 2 samples taken during the calendar week, no less than 48 hours apart

#### **BASIS DESCRIPTIONS**

- 1. VPDES Permit Regulation (9 VAC 25-31)
- 2. Federal Effluent Requirements (Secondary Treatment Regulation 40CFR133)
- 3. Water Quality Standards (9 VAC 25-260)
- 4. DEQ Regional Stream Model
- 5. Best Professional Judgment (BPJ)

<sup>\* =</sup> Applicable only when chlorination is used for disinfection

<sup>\*\* =</sup> Applicable if an alternative to chlorination is used for disinfection.

Outfall 002 Final Limits Design Flow: 0.075 MGD

	BASIS FOR	EFFLUENT LIMITATIONS				MONITORING REQ	UIREMENTS
PARAMETER	LIMITS	Monthly Average		Maximum		Frequency	Sample Type
Flow (MGD)	1	N	L	NL		Continuous	TIRE
		Monthly	Average	Weekly Average			
cBOD <sub>5</sub> (Jun-Dec)	3,4,5	12 mg/L	3.4 kg/d	18 mg/L	5.1 kg/d	1/Week	4 HC
cBOD <sub>5</sub> (Jan-May)	2,3,4,5	25 mg/L	7.1 kg/d	40 mg/L	11 kg/d	1/Week	4 HC
Ammonia-N (Jun-Nov)(mg/L)	1,3	5.	.9	5	.9	1/Month	4 HC
TSS	1	30 mg/L	8.5 kg/d	45 mg/L	13 kg/d	1/Month	4 HC
Effluent Chlorine (TRC)(mg/L)*	3	0.012		0.014		3/Day at 4-hr intervals	Grab
E. coli (N/100 mL) (geometric mean)	3	12	26	N	A	4/Month* or 2/Week** 10 am to 4 pm	Grab
Copper, TR (µg/L)	3	1	7	17		1/Month	4 HC
Zinc, TR (µg/L)	3	15	50	150		1/Month	4 HC
		Minimum		Maxi	mum		
pH (S.U.)	2,3	6.0		9	.0	1/Day	Grab
Dissolved Oxygen (mg/L)	3,4	7.6		NA		1/Day	Grab
Contact Chlorine (TRC)(mg/L)*	3,5	1.	.0	NA		3/Day at 4-hr intervals	Grab
Total Hardness (as CaCO <sub>3</sub> )(mg/L)	5	N	L	N	A	1/Quarter	4 HC

 $NL = No\ Limitation,\ monitoring\ required$ 

NA = Not Applicable

TIRE = Totalizing, Indicating, and Recording equipment

4 HC = 4-Hour Composite

4/Month=4 samples taken monthly, with at least 1 sample taken each calendar week

2/Week = 2 samples taken during the calendar week, no less than 48 hours apart

#### **BASIS DESCRIPTIONS**

- 1. VPDES Permit Regulation (9 VAC 25-31)
- 2. Federal Effluent Requirements (Secondary Treatment Regulation 40CFR133)
- 3. Water Quality Standards (9 VAC 25-260)
- 4. DEQ Regional Stream Model
- 5. Best Professional Judgment (BPJ)

<sup>\* =</sup> Applicable only when chlorination is used for disinfection

<sup>\*\* =</sup> Applicable if an alternative to chlorination is used for disinfection.

Outfall 002 Final Limits Design Flow: 0.099 MGD

	BASIS FOR	EFFLUENT LIMITATIONS				MONITORING REQ	UIREMENTS
PARAMETER	LIMITS	Monthly Average		Maximum		Frequency	Sample Type
Flow (MGD)	1	N	L	NL		Continuous	TIRE
		Monthly	Monthly Average		Average		
cBOD <sub>5</sub> (Jun-Dec)	3,4,5	11 mg/L	4.1 kg/d	16 mg/L	6.0 kg/d	1/Week	4 HC
cBOD <sub>5</sub> (Jan-May)	2,3,4,5	25 mg/L	9.4 kg/d	40 mg/L	15 kg/d	1/Week	4 HC
Ammonia-N (Jun-Nov)(mg/L)	1,3	5.	.0	5	.0	1/Month	4 HC
TSS	1	30 mg/L	11 kg/d	45 mg/L	17 kg/d	1/Month	4 HC
Effluent Chlorine (TRC)(mg/L)*	3	0.011		0.013		3/Day at 4-hr intervals	Grab
E. coli (N/100 mL) (geometric mean)	3	12	26	N	A	4/Month* or 2/Week** 10 am to 4 pm	Grab
Copper, TR (µg/L)	3	1	6	1	6	1/Month	4 HC
Zinc, TR (µg/L)	3	12	20	120		1/Month	4.HC
		Minimum		Maxi	mum		
pH (S.U.)	2,3	6.0		9	.0	1/Day	Grab
Dissolved Oxygen (mg/L)	3,4	7.	.6	NA		1/Day	Grab
Contact Chlorine (TRC)(mg/L)*	3,5	1.	.0	NA		3/Day at 4-hr intervals	Grab
Total Hardness (as CaCO <sub>3</sub> )(mg/L)	5	N	L	NA		1/Quarter	4 HC

 $NL = No\ Limitation,\ monitoring\ required$ 

NA = Not Applicable

TIRE = Totalizing, Indicating, and Recording equipment

4 HC = 4 - Hour Composite

4/Month = 4 samples taken monthly, with at least 1 sample taken each calendar week

2/Week = 2 samples taken during the calendar week, no less than 48 hours apart

#### **BASIS DESCRIPTIONS**

- 1. VPDES Permit Regulation (9 VAC 25-31)
- 2. Federal Effluent Requirements (Secondary Treatment Regulation 40CFR133)
- 3. Water Quality Standards (9 VAC 25-260)
- 4. DEQ Regional Stream Model
- 5. Best Professional Judgment (BPJ)

<sup>\* =</sup> Applicable only when chlorination is used for disinfection

<sup>\*\* =</sup> Applicable if an alternative to chlorination is used for disinfection.

#### LIMITING FACTORS – OVERVIEW:

The following potential limiting factors have been considered in developing this permit and fact sheet:

Water Quality Management Plan Regulation (WQMP) (9 VAC 25-720)	
A. TMDL limits	None
B. Non-TMDL WLAs	BOD <sub>5</sub>
C. CBP (TN & TP) WLAs	None
Federal Effluent Guidelines	cBOD <sub>5</sub> , TSS, pH
BPJ/Agency Guidance limits	TRC (contact)
Water Quality-based Limits - numeric	cBOD <sub>5</sub> , DO, TKN, Ammonia-N, TRC (effluent), E. coli, pH, Cadmium, Copper, Zinc
Water Quality-based Limits - narrative	None
Technology-based Limits (9 VAC 25-40-70)	None
Whole Effluent Toxicity (WET)	Not applicable
Storm Water Limits	Not applicable

#### EVALUATION OF THE EFFLUENT – CONVENTIONAL POLLUTANTS:

This discharge is included in the North Creek DO model maintained by the DEQ-Valley Regional Office, which is available for review by visitation or electronically upon request.

The DO model demonstrated that the values shown below are protective:

	0.060	MGD	0.075	MGD	0.09	9 MGD
	(Jun-Nov)	(Dec-May)	(Jun-Nov)	(Dec-May)	(Jun-Nov)	(Dec-May)
cBOD <sub>5</sub> (mg/L)	12	25	12	25	11	25
TKN (mg/L)	7.4	12.5	6.8	12.5	6.3	12.5
DO (mg/L)	7.6	7.6	7.6	7.6	7.6	7.6

cBOD<sub>5</sub> limits have been carried forward from the previous reissuance. This discharge is identified in the WQMP Regulation and has been allocated 14.07 kg BOD<sub>5</sub> per day for the discharge to North Creek. The effluent limits for oxygen demanding substances are expressed as cBOD<sub>5</sub> instead of BOD<sub>5</sub> (nBOD<sub>5</sub> + cBOD<sub>5</sub>), however, if the cBOD<sub>5</sub> was as much as the highest BOD<sub>5</sub> allowed (30 mg/L), at the current design flow (0.099 MGD) the discharge would remain in conformance with the WQMP waste load allocation (WLA).

TKN (Jun-Nov) limits were removed at this reissuance and replaced with Ammonia-N (Jun-Nov) limits. This does not violate antibacksliding requirements because the modeled effluent TKN was more than two times the Ammonia-N WLA and it was determined that the Ammonia-N limits imposed in this permit will control TKN at concentrations lower than previously permitted. TKN (Dec-May) limits were determined to not be necessary because the effluent data submitted during the previous permit indicates the facility is consistently achieving TKN concentrations that are less than 10% of the modeled TKN (Dec-May) value.

The TSS limits are consistent with the Secondary Treatment Regulation and have been carried forward from the previous permit.

The pH limits reflect the current WQS for pH in the receiving stream and have been carried forward from the previous permit.

#### EVALUATION OF THE EFFLUENT – DISINFECTION:

This facility currently utilizes UV disinfection. The monitoring frequency for E. coli has been revised from 1/Week to 2/Week in accordance with current guidance. Chlorine limits are also specified in the permit, but are only applicable should the facility need to utilize chlorine disinfection. An E. coli limit with 4/Month monitoring is required if chlorination is utilized for disinfection.

#### EVALUATION OF THE EFFLUENT – NUTRIENTS:

The design average flow for the facility as it existed on or before July 1, 2005 is 0.099 MGD. The design of this treatment works did not take into consideration the need for nutrient removal.

The "permitted design capacity" or "permitted capacity" in terms of annual mass load of total nitrogen or total phosphorous discharged by this non-significant discharger is assumed to be that achieved at the current design flow using the currently installed technology.

Future nutrient limitations may apply to this facility. For the sole purpose of establishing the current mass load of nutrients discharged from this facility, it is recognized that the design flow is 0.099 MGD (see above) and the technology installed for treating domestic sewage did not intentionally consider nutrient removal.

Pursuant to section 62.1-44.19:12 - :19 of the law, Total Nitrogen (TN) and Total Phosphorus (TP) baselines are being established for this facility to represent nutrient discharge allowances as of July 1, 2005. Once established, these baselines will be used as a limiting factor should the facility ever expand or have a significant increase in effluent TN or TP concentrations. For municipal facilities, the baselines are based on the permitted design capacity of the facility. The permitted design capacity is defined as

Total N or P (lb/yr) = concentration (mg/L) x design flow (MGD) x 8.3438 x 365 (days/yr)

where

Design flow – as of July 1, 2005, the approved flow was 0.099 MGD Concentration – the treatment provided as of July 1, 2005 was TN = 18.7 mg/L and TP = 2.5 mg/L (assumed concentrations based on secondary treatment facility)

#### 0.099 MGD

 $TN = 18.7 \text{ mg/L} \times 0.099 \text{ MGD} \times 8.3438 \times 365 \text{ days/yr} = 5,638 \text{ lb/yr}$  $TP = 2.5 \text{ mg/L} \times 0.099 \text{ MGD} \times 8.3438 \times 365 \text{ days/yr} = 754 \text{ lb/yr}$ 

#### **EVALUATION OF THE EFFLUENT – TOXICS:**

#### Stream:

Water quality data for the receiving stream were obtained from Ambient Monitoring Station No. 2CXB005.39 at the Route 660 Bridge on Cunningham Creek and have been carried forward since no new data was available. A Flow Frequency Determination for the receiving stream was generated April 15, 2012, and is included in Appendix A. The "Wet Season" or "High Flow" months are December through May.

	Str	eam Information	
90% Annual Temp (°C) =	22	90% pH (SU) =	7.7
90% Wet Temp (°C) =	12.8	10% pH (SU) =	6.3
Mean Hardness (mg/L) =	50		

All toxic pollutants, including Ammonia-N and TRC, are assumed absent in the receiving stream because there are no data for these parameters directly above the discharge.

#### Discharge:

The pH and temperature values were obtained from data submitted by the permittee. The hardness value has been carried forward from the previous permit.

	Effluent Inf	formation	
90% Annual Temp (°C) =	26	90% pH (SU) =	7.9
90% Wet Temp (°C) =	21	10% pH (SU) =	7.3
Mean Hardness (mg/L) =	105.6		

WQC and WLAs were calculated for the WQS parameters for which data are available. The resulting WQC and WLAs are presented in this appendix. Current agency guidelines recommends the evaluation of toxic pollutant limits for TRC and Ammonia-N be based on default effluent concentrations of 20 mg/L and 9 mg/L, respectively. The effluent data were analyzed per the protocol for evaluation of effluent toxic pollutants included in this appendix with the following results:

- TRC: Slightly more stringent TRC limits have been included based on new stream flow data. Because the facility currently utilizes UV disinfection, a compliance schedule for meeting the more stringent limits has not been included.
- Ammonia-N: Ammonia-N (Dec-May) limits were removed. This does not violate antibacksliding requirements because removal of the limits is based on new effluent temperature and pH data. Ammonia-N (Jun-Nov) limits were determined to be necessary at this reissuance and have replaced the previous TKN (Jun-Nov) limits. No compliance schedule has been included for the new Ammonia-N limits because based on existing effluent data, the facility can consistently meet the new limits.

#### Metals:

- Cadmium: New effluent data for cadmium were available during this reissuance. Based on the evaluation using the new effluent data obtained during the term of the previous permit along with the datum from the previous permit that resulted in the determination that limits were required, no limits were determined to be necessary for cadmium at this reissuance; therefore, the limits and monitoring of the previous permit have been removed. If the new effluent information had been available at the previous reissuance, it would have been determined that there was not a reasonable potential for cadmium to violate WQS.
- Copper: More stringent copper limits were determined to be necessary at the 0.060 MGD and 0.075 MGD flow tiers. The copper limit at the 0.099 MGD tier was determined to be the same as in the previous permit and has been carried forward.
- Zinc: Limits for zinc were imposed at the previous reissuance at the 0.099 MGD flow tier. Less stringent zinc limits were determined to be necessary at the 0.099 MGD tier at this reissuance; however, the previous limits were carried forward to comply with antibacksliding requirements. At this reissuance, limits for zinc were determined to be necessary at the 0.060 MGD and the 0.075 MGD flow tiers.
- ? Hardness: Monitoring for hardness has been included at this reissuance per BPJ in order to obtain more data on this effluent characteristic that is used in determining limits for metals.

Additional monitoring data is needed for a number of pollutants due to the lack of effluent quality data. The permittee must monitor the effluent at Outfall 002 for the substances noted in Attachment A of the permit within one year of the permit's effective date.

## WQC-WLA SPREADSHEET INPUT – 0.060 MGD

#### WATER QUALITY CRITERIA / WASTE LOAD ALLOCATION ANALYSIS

Facility Name:

Fork Union Military Academy STP

 Receiving Stream:
 Permit No.:
 VA0024147

 North Creek
 Date:
 5/7/2012

Stream Information		Stream Flows		Mixing Information			Effluent Information	
Mean Hardness (as CaCO3) =	50 mg/L	1Q10 (Annual) =	0.0322 MGD	Annual	- 1Q10 Flow =	100 %	Mean Hardness (as CaCO3) =	105.6 mg/L
90% Temperature (Annual) =	22 deg C	7Q10 (Annual) =	0.0372 MGD		- 7Q10 Flow =	100 %	90% Temp (Annual) =	26 deg C
90% Temperature (Wet season) =	12.8 deg C	30Q10 (Annual) =	0.0554 MGD		- 30Q10 Flow =	100 %	90% Temp (Wet season) =	21 deg C
90% Maximum pH =	7.7 SU	1Q10 (Wet season) =	0.151 MGD	Wet Season	- 1Q10 Flow =	100 %	90% Maximum pH =	7.9 SU
10% Maximum pH =	6.3 SU	30Q10 (Wet season) =	0.2331 MGD		- 30Q10 Flow =	100 %	10% Maximum pH =	7.3 SU
Tier Designation =	1	30Q5 =	0.0835 MGD				Current Discharge Flow =	0.060 MGD
Public Water Supply (PWS) Y/N? =	N	Harmonic Mean =	0.213 MGD				Discharge Flow for Limit Analysis =	0.060 MGD
V(alley) or P(iedmont)? =	V							
Trout Present Y/N? =	N							
Early Life Stages Present Y/N? =	Υ							

#### Footnotes:

- 1. All concentrations expressed as micrograms/liter (ug/l), unless noted otherwise
- 2. All flow values are expressed as Million Gallons per Day (MGD).
- 3. Discharge volumes are highest monthly average or 2C maximum for Industries and design flows for Municipals.
- 4. Hardness expressed as mg/l CaCO3. Standards calculated using Hardness values in the range of 25-400 mg/l CaCO3.
- 5. "Public Water Supply" protects for fish & water consumption. "Other Surface Waters" protects for fish consumption only.
- 5. Fubilic Water Supply protects for fish & water consumption. Other Surface Waters protects for its
- 6. Carcinogen "Y" indicates carcinogenic parameter.
- 7. Ammonia WQSs selected from separate tables, based on pH and temperature
- 8. Metals measured as Dissolved, unless specified otherwise.
- 9. WLA = Waste Load Allocation (based on standards).

- 10. WLA = Waste Load Allocation (based on standards).
- 11. WLAs are based on mass balances (less background, if data exist).
- 12. Acute 1 hour avg. concentration not to be exceeded more than 1/3 years.
- 13. Chronic 4 day avg. concentration (30 day avg. for Ammonia) not to be exceeded more than 1/3 years.
- 14. Mass balances employ 1Q10 for Acute, 30Q10 for Chronic Ammonia, 7Q10 for Other Chronic, 30Q5 for Non-carcinogens, and Harmonic Mean for Carcinogens. Actual flows employed are a function of the mixing analysis and may be less than the actual flows.

Version: OWP Guidance Memo 00-2011 (8/24/00)

15. Effluent Limitations are calculated elsewhere using the minimum WLA and EPA's statistical approach (Technical Support Document).

## WQC-WLA SPREADSHEET OUTPUT – 0.060MGD

Facility Name:	Permit No.:														
Fork Union Military Academy STP	VA0024147	w	ATER QUAI	LITY CRITE	RIA				WAT	ER QUALIT	Y CRITER	IA	NON-ANT	TIDEGRADATI	ION
Receiving Stream:	Date:	0.060	MGD Discharge	e Flow - 100% S	tream Mix				0.060	MGD Discharge	Flow - Mix pe	er "Mixer"	WASTE LO	AD ALLOCA	TIONS
North Creek	5/7/2012			Humar	Health						Huma	n Health	0.060 MGD	Discharge - Mix p	per "Mixer'
		Aquatic P	rotection	Public Water	Other Surfac	INSTRE	AM BASELIN	IES	Aquatic Prot	ection	Public Water	Other Surface	Aquatic Prot	ection	Human
Toxic Parameter and Form	Carcinogen?	Acute	Chronic	Supplies	Waters	Acute	Chronic	H-Health	Acute	Chronic	Supplies	Waters	Acute	Chronic	Health
Ammonia-N (Annual)	N	1.2E+01 n	1.7E+00 mg/L	None	None	2.9E+00 mg/L	4.3E-01 mg/l	None	1.2E+01 mg/L	1.7E+00 mg/L	None	None	1.8E+01 mg/L	3.3E+00 mg/L	N/A
Ammonia-N (Wet Season)	N	1.3E+01 n	3.4E+00 mg/L	L None	None	3.3E+00 mg/L	8.6E-01 mg/L	None	1.3E+01 mg/L	3.4E+00 mg/L	None	None	4.7E+01 mg/L	1.7E+01 mg/L	N/A
Cadmium	N	3.3E+00	9.9E-01	5.0E+00	None	8.3E-01	2.5E-01	None	3.3E+00	9.9E-01	5.0E+00	None	5.1E+00	1.6E+00	N/A
Chlorine, Total Residual	N	1.9E-02 n	1.1E-02 mg/L	L None	None	4.8E-03 mg/L	2.8E-03 mg/L	None	1.9E-02 mg/L	1.1E-02 mg/L	None	None	2.9E-02 mg/L	1.8E-02 mg/L	N/A
Copper	N	1.2E+01	7.7E+00	1.3E+03	None	2.9E+00	1.9E+00	None	1.2E+01	7.7E+00	1.3E+03	None	1.8E+01	1.3E+01	N/A
Selenium, Total Recoverable	N	2.0E+01	5.0E+00	1.7E+02	4.2E+03	5.0E+00	1.3E+00	4.2E+02	2.0E+01	5.0E+00	1.7E+02	4.2E+03	3.1E+01	8.1E+00	1.0E+04
Silver	N	2.7E+00	None	None	None	6.7E-01	None	None	2.7E+00	None	None	None	4.1E+00	N/A	N/A
Zinc	N	1.0E+02	1.0E+02	7.4E+03	2.6E+04	2.6E+01	2.6E+01	2.6E+03	1.0E+02	1.0E+02	7.4E+03	2.6E+04	1.6E+02	1.7E+02	6.2E+04

#### WQC-WLA SPREADSHEET INPUT – 0.075 MGD

#### WATER QUALITY CRITERIA / WASTE LOAD ALLOCATION ANALYSIS

Facility Name:

Fork Union Military Academy STP

 Receiving Stream:
 Permit No.: VA0024147

 North Creek
 Date: 5/7/2012

Version: OWP Guidance Memo 00-2011 (8/24/00)

Stream Information		Stream Flows		Mixing Information	า		Effluent Information	
Mean Hardness (as CaCO3) =	50 mg/L	1Q10 (Annual) =	0.0322 MGD	Annual	- 1Q10 Flow =	100 %	Mean Hardness (as CaCO3) =	105.6 mg/L
90% Temperature (Annual) =	22 deg C	7Q10 (Annual) =	0.0372 MGD		- 7Q10 Flow =	100 %	90% Temp (Annual) =	26 deg C
90% Temperature (Wet season) =	12.8 deg C	30Q10 (Annual) =	0.0554 MGD		- 30Q10 Flow =	100 %	90% Temp (Wet season) =	21 deg C
90% Maximum pH =	7.7 SU	1Q10 (Wet season) =	0.151 MGD	Wet Season	- 1Q10 Flow =	100 %	90% Maximum pH =	7.9 SU
10% Maximum pH =	6.3 SU	30Q10 (Wet season) =	0.2331 MGD		- 30Q10 Flow =	100 %	10% Maximum pH =	7.3 SU
Tier Designation =	1	30Q5 =	0.0835 MGD				Current Discharge Flow=	0.075 MGD
Public Water Supply (PWS) Y/N? =	N	Harmonic Mean =	0.213 MGD				Discharge Flow for Limit Analysis =	0.075 MGD
V(alley) or P(iedmont)? =	V							
Trout Present Y/N? =	N							
Early Life Stages Present Y/N? =	Υ							

#### Footnotes:

- 1. All concentrations expressed as micrograms/liter (ug/l), unless noted otherwise
- 2. All flow values are expressed as Million Gallons per Day (MGD).
- R. Discharge volumes are highest monthly average or 2C maximum for Industries and design flows for Municipals
- 4. Hardness expressed as mg/l CaCO3. Standards calculated using Hardness values in the range of 25-400 mg/l CaCO3.
- $5. \ "Public Water Supply" \ protects for fish \& water consumption. \ "Other Surface Waters" \ protects for fish consumption only.$
- 6. Carcinogen "Y" indicates carcinogenic parameter.
- 7. Ammonia WQSs selected from separate tables, based on pH and temperature.
- 8. Metals measured as Dissolved, unless specified otherwise.
- 9. WLA = Waste Load Allocation (based on standards).

- 10. WLA = Waste Load Allocation (based on standards).
- 11. WLAs are based on mass balances (less background, if data exist).
- 2. Acute 1 hour avg. concentration not to be exceeded more than 1/3 years.
- 13. Chronic 4 day avg. concentration (30 day avg. for Ammonia) not to be exceeded more than 1/3 years.
- 14. Mass balances employ 1Q10 for Acute, 30Q10 for Chronic Ammonia, 7Q10 for Other Chronic, 30Q5 for Non-carcinogens, and Harmonic Mean for Carcinogens. Actual flows employed are a function of the mixing analysis and may be less than the actual flows.
- 15. Effluent Limitations are calculated elsewhere using the minimum WLA and EPA's statistical approach (Technical Support Document).

## WQC-WLA SPREADSHEET OUTPUT – 0.075 MGD

Facility Name:	Permit No.:														
IX Union Military Academy S	VA0024147	WATE	R QUALITY	CRITERIA					w	ATER QUALIT	Y CRITER	IA	NON-ANT	TIDEGRADATI	ON
Receiving Stream:	Date:	0.075	MGD Discharge I	Flow - 100% Str	ream Mix				0.	.075 MGD Discharg	ge Flow - Mix p	oer "Mixer"	WASTE LO	AD ALLOCA	TIONS
North Creek	5/7/2012			Human I	Health						Human	Health	0.075 MGD	Discharge - Mix	per "Mixer
		Aquatic Prote	ection	Public Water C	Other Surface	INSTRE	AM BASELINE	s	Aquatic	Protection	Public Water	Other Surface	Aquatic Prof	ection	Human
Toxic Parameter and Form	Carcinogen?	Acute	Chronic	Supplies	Waters	Acute	Chronic	H-Health	Acute	Chronic	Supplies	Waters	Acute	Chronic	Health
Ammonia-N (Annual)	N	1.2E+01 mg/L	1.7E+00 mg/L	None	None	2.9E+00 mg/L	4.2E-01 mg/L	None	1.2E+01 m	ng/L 1.7E+00 mg/l	None	None	1.6E+01 mg/L	2.9E+00 mg/L	N/A
Ammonia-N (Wet Season)	N	1.3E+01 mg/L	3.4E+00 mg/L	None	None	3.3E+00 mg/L	8.4E-01 mg/L	None	1.3E+01 m	ng/L 3.4E+00 mg/l	L None	None	3.9E+01 mg/L	. 1.4E+01 mg/L	N/A
Cadmium	N	3.4E+00	1.0E+00	5.0E+00	None	8.6E-01	2.5E-01	None	3.4E+00	1.0E+00	5.0E+00	None	4.9E+00	1.5E+00	N/A
Chlorine, Total Residual	N	1.9E-02 mg/L	1.1E-02 mg/L	None	None	4.8E-03 mg/L	2.8E-03 mg/L	None	1.9E-02 m	ng/L 1.1E-02 mg/l	L None	None	2.7E-02 mg/L	. 1.6E-02 mg/L	N/A
Copper	N	1.2E+01	8.0E+00	1.3E+03	None	3.0E+00	2.0E+00	None	1.2E+01	8.0E+00	1.3E+03	None	1.7E+01	1.2E+01	N/A
Selenium, Total Recoverable	N N	2.0E+01	5.0E+00	1.7E+02	4.2E+03	5.0E+00	1.3E+00	4.2E+02	2.0E+01	5.0E+00	1.7E+02	4.2E+03	2.9E+01	7.5E+00	8.9E+03
Silver	N	2.8E+00	None	None	None	7.0E-01	None	None	2.8E+00	None	None	None	4.0E+00	N/A	N/A
Zinc	N	1.1E+02	1.1E+02	7.4E+03	2.6E+04	2.7E+01	2.6E+01	2.6E+03	1.1E+02	1.1E+02	7.4E+03	2.6E+04	1.5E+02	1.6E+02	5.5E+04

## WQC-WLA SPREADSHEET INPUT – 0.099 MGD

#### WATER QUALITY CRITERIA / WASTE LOAD ALLOCATION ANALYSIS

Facility Name:

Fork Union Military Academy STP

Permit No.: VA0024147 Receiving Stream: North Creek Date: 5/7/2012

Stream Information		Stream Flows		Mixing Information	n		Effluent Information	
Mean Hardness (as CaCO3) =	50 mg/L	1Q10 (Annual) =	0.0322 MGD	Annual	- 1Q10 Flow =	100 %	Mean Hardness (as CaCO3) =	105.6 mg/L
90% Temperature (Annual) =	22 deg C	7Q10 (Annual) =	0.0372 MGD		- 7Q10 Flow =	100 %	90% Temp (Annual) =	26 deg C
90% Temperature (Wet season) =	12.8 deg C	30Q10 (Annual) =	0.0554 MGD		- 30Q10 Flow =	100 %	90% Temp (Wet season) =	21 deg C
90% Maximum pH =	7.7 SU	1Q10 (Wet season) =	0.151 MGD	Wet Season	- 1Q10 Flow =	100 %	90% Maximum pH =	7.9 SU
10% Maximum pH =	6.3 SU	30Q10 (Wet season) =	0.2331 MGD		- 30Q10 Flow =	100 %	10% Maximum pH =	7.3 SU
Tier Designation =	1	30Q5 =	0.0835 MGD				Current Discharge Flow =	0.099 MGD
Public Water Supply (PWS) Y/N? =	N	Harmonic Mean =	0.213 MGD				Discharge Flow for Limit Analysis =	0.099 MGD
V(alley) or P(iedmont)? =	V							
Trout Present Y/N? =	N							
Early Life Stages Present Y/N? =	Υ							

#### Footnotes:

- 1. All concentrations expressed as micrograms/liter (ug/l), unless noted otherwise.
- 2. All flow values are expressed as Million Gallons per Day (MGD).
- 3. Discharge volumes are highest monthly average or 2C maximum for Industries and design flows for Municipals.
- $4. \ \ Hardness \ expressed \ as \ mg/l \ CaCO3. \ \ Standards \ calculated \ using \ Hardness \ values \ in the \ range \ of \ 25-400 \ mg/l \ CaCO3.$
- $5. \ "Public Water Supply" \ protects for fish \& water consumption. \ "Other Surface Waters" \ protects for fish consumption only.$
- 6. Carcinogen "Y" indicates carcinogenic parameter.
- 7. Ammonia WQSs selected from separate tables, based on pH and temperature.
- 8. Metals measured as Dissolved, unless specified otherwise
- 9. WLA = Waste Load Allocation (based on standards).

- 10. WLA = Waste Load Allocation (based on standards).
- 11. WLAs are based on mass balances (less background, if data exist).
- 12. Acute 1 hour avg. concentration not to be exceeded more than 1/3 years
- 13. Chronic 4 day avg. concentration (30 day avg. for Ammonia) not to be exceeded more than 1/3 years
- and Harmonic Mean for Carcinogens. Actual flows employed are a function of the mixing analysis and may be less than the actual flows

Version: OWP Guidance Memo 00-2011 (8/24/00)

15. Effluent Limitations are calculated elsewhere using the minimum WLA and EPA's statistical approach (Technical Support Document).

## WQC-WLA SPREADSHEET OUTPUT – 0.099 MGD

Facility Name:	Permit No.:														
Fork Union Military Academy STP	VA0024147	WAT	ER QUALITY	CRITERI	Α				WA	TER QUALITY	CRITERI	Α	NON-ANT	TIDEGRADATIO	N
Receiving Stream:	Date:	0.099	MGD Discharge	Flow - 100%	Stream Mix				0.09	9 MGD Discharge	Flow - Mix pe	er "Mixer"	WASTE LO	AD ALLOCAT	IONS
North Creek	5/7/2012	•		Human	Health						Human	Health	0.099 MGD D	ischarge - Mix per	"Mixer"
		Aquatic Prof	tection P	ublic WaterO	ther Surface	INSTRI	EAM BASELIN	ES	Aquatic Pro	otection	Public Water	Other Surface	Aquatic Prote	ection	Human
Toxic Parameter and Form	Carcinogen?	Acute	Chronic	Supplies	Waters	Acute	Chronic	H-Health	Acute	Chronic	Supplies	Waters	Acute	Chronic	Health
Acenaphthene	N	None	None	6.7E+02	9.9E+02	None	None	9.9E+01	None	None	6.7E+02	9.9E+02	N/A	N/A	1.8E+03
Acrolein	N	None	None	6.1E+00	9.3E+00	None	None	9.3E-01	None	None	6.1E+00	9.3E+00	N/A	N/A	1.7E+01
Acrylonitrile	Υ	None	None	5.1E-01	2.5E+00	None	None	2.5E-01	None	None	5.1E-01	2.5E+00	N/A	N/A	7.9E+00
Aldrin	Υ	3.0E+00	None	4.9E-04	5.0E-04	7.5E-01	None	5.0E-05	3.0E+00	None	4.9E-04	5.0E-04	4.0E+00	N/A	1.6E-03
Ammonia-N (Annual)	N	1.1E+01 mg/L	1.6E+00 mg/L	None	None	2.8E+00 mg/L	4.1E-01 mg/L	None	1.1E+01 mg/l	_ 1.6E+00 mg/L	None	None	1.5E+01 mg/L	2.5E+00 mg/L	N/A
Ammonia-N (Wet Season)	N	1.3E+01 mg/L	3.2E+00 mg/L	None	None	3.2E+00 mg/L	8.1E-01 mg/L	None	1.3E+01 mg/l	3.2E+00 mg/L	None	None	3.2E+01 mg/L	1.1E+01 mg/L	N/A
Anthracene	N	None	None	8.3E+03	4.0E+04	None	None	4.0E+03	None	None	8.3E+03	4.0E+04	N/A	N/A	7.4E+04
Antimony	N	None	None	5.6E+00	6.4E+02	None	None	6.4E+01	None	None	5.6E+00	6.4E+02	N/A	N/A	1.2E+03
Arsenic	N	3.4E+02	1.5E+02	1.0E+01	None	8.5E+01	3.8E+01	None	3.4E+02	1.5E+02	1.0E+01	None	4.5E+02	2.1E+02	N/A
Barium	N	None	None	2.0E+03	None	None	None	None	None	None	2.0E+03	None	N/A	N/A	N/A
Benzene	Υ	None	None	2.2E+01	5.1E+02	None	None	5.1E+01	None	None	2.2E+01	5.1E+02	N/A	N/A	1.6E+03
Benzidine	Υ	None	None	8.6E-04	2.0E-03	None	None	2.0E-04	None	None	8.6E-04	2.0E-03	N/A	N/A	6.3E-03
Benzo(a)anthracene	Υ	None	None	3.8E-02	1.8E-01	None	None	1.8E-02	None	None	3.8E-02	1.8E-01	N/A	N/A	5.7E-01
Benzo(a)pyrene	Υ	None	None	3.8E-02	1.8E-01	None	None	1.8E-02	None	None	3.8E-02	1.8E-01	N/A	N/A	5.7E-01
Benzo(b)fluoranthene	Υ	None	None	3.8E-02	1.8E-01	None	None	1.8E-02	None	None	3.8E-02	1.8E-01	N/A	N/A	5.7E-01
Benzo(k)fluoranthene	Υ	None	None	3.8E-02	1.8E-01	None	None	1.8E-02	None	None	3.8E-02	1.8E-01	N/A	N/A	5.7E-01
Bis2-Chloroethyl Ether	Υ	None	None	3.0E-01	5.3E+00	None	None	5.3E-01	None	None	3.0E-01	5.3E+00	N/A	N/A	1.7E+01
Bis2-Chloroisopropyl Ether	N	None	None	1.4E+03	6.5E+04	None	None	6.5E+03	None	None	1.4E+03	6.5E+04	N/A	N/A	1.2E+05
Bis2-Ethylehexyl Phthalate	Υ	None	None	1.2E+01	2.2E+01	None	None	2.2E+00	None	None	1.2E+01	2.2E+01	N/A	N/A	6.9E+01
Bromoform	Υ	None	None	4.3E+01	1.4E+03	None	None	1.4E+02	None	None	4.3E+01	1.4E+03	N/A	N/A	4.4E+03
Butyl Benzyl Phthalate	N	None	None	1.5E+03	1.9E+03	None	None	1.9E+02	None	None	1.5E+03	1.9E+03	N/A	N/A	3.5E+03
Cadmium	N	3.6E+00	1.0E+00	5.0E+00	None	8.9E-01	2.6E-01	None	3.6E+00	1.0E+00	5.0E+00	None	4.7E+00	1.4E+00	N/A
Carbon Tetrachloride	Υ	None	None	2.3E+00	1.6E+01	None	None	1.6E+00	None	None	2.3E+00	1.6E+01	N/A	N/A	5.0E+01
Chlordane	Υ	2.4E+00	4.3E-03	8.0E-03	8.1E-03	6.0E-01	1.1E-03	8.1E-04	2.4E+00	4.3E-03	8.0E-03	8.1E-03	3.2E+00	5.9E-03	2.6E-02
Chloride	N	8.6E+02 mg/L	2.3E+02 mg/L	2.5E+02 n	None	2.2E+02 mg/L	5.8E+01 mg/L	None	8.6E+02 mg/l	L 2.3E+02 mg/L	2.5E+02 n	r None	1.1E+03 mg/L	3.2E+02 mg/L	N/A
Chlorine, Total Residual	N	1.9E-02 mg/L	1.1E-02 mg/L	None	None	4.8E-03 mg/L	2.8E-03 mg/L	None	1.9E-02 mg/l	L 1.1E-02 mg/L	None	None	2.5E-02 mg/L	1.5E-02 mg/L	N/A
Chlorobenzene	N	None	None	1.3E+02	1.6E+03	None	None	1.6E+02	None	None	1.3E+02	1.6E+03	N/A	N/A	2.9E+03
Chlorodibromomethane	Υ	None	None	4.0E+00	1.3E+02	None	None	1.3E+01	None	None	4.0E+00	1.3E+02	N/A	N/A	4.1E+02
Chloroform	N	None	None	3.4E+02	1.1E+04	None	None	1.1E+03	None	None	3.4E+02	1.1E+04	N/A	N/A	2.0E+04
2-Chloronaphthalene	N	None	None	1.0E+03	1.6E+03	None	None	1.6E+02	None	None	1.0E+03	1.6E+03	N/A	N/A	2.9E+03
2-Chlorophenol	N	None	None	8.1E+01	1.5E+02	None	None	1.5E+01	None	None	8.1E+01	1.5E+02	N/A	N/A	2.8E+02
Chlorpyrifos	N	8.3E-02	4.1E-02	None	None	2.1E-02	1.0E-02	None	8.3E-02	4.1E-02	None	None	1.1E-01	5.6E-02	N/A

Chromium (+3)	N	5.3E+02	6.8E+01	None	None	1.3E+02	1.7E+01	None	5.3E+02	6.8E+01	None	None	7.0E+02	9.4E+01	N/A
Chromium (+6)	N	1.6E+01	1.1E+01	None	None	4.0E+00	2.8E+00	None	1.6E+01	1.1E+01	None	None	2.1E+01	1.5E+01	N/A
Total Chromium	N	None	None	1.0E+02	None	None	None	None	None	None	1.0E+02	None	N/A	N/A	N/A
Chrysene	Υ	None	None	3.8E-03	1.8E-02	None	None	1.8E-03	None	None	4.4E-02	4.9E-01	N/A	N/A	1.5E+00
Copper	N	1.2E+01	8.2E+00	1.3E+03	None	3.1E+00	2.1E+00	None	1.2E+01	8.2E+00	1.3E+03	None	1.6E+01	1.1E+01	N/A
Cyanide, Free	N	2.2E+01	5.2E+00	1.4E+02	1.6E+04	5.5E+00	1.3E+00	1.6E+03	2.2E+01	5.2E+00	1.4E+02	1.6E+04	2.9E+01	7.2E+00	2.9E+04
DDD	Y	None	None	3.1E-03	3.1E-03	None	None	3.1E-04	None	None	3.1E-03	3.1E-03	N/A	N/A	9.8E-03
DDE DDT	Y Y	None 1.15.00	None 1.0E-03	2.2E-03 2.2E-03	2.2E-03 2.2E-03	None 2.8E-01	None 2.5E-04	2.2E-04 2.2E-04	None 1.1E+00	None 1.0E-03	2.2E-03 2.2E-03	2.2E-03 2.2E-03	N/A 1.5E+00	N/A 1.4E-03	6.9E-03 6.9E-03
Demeton	N	1.1E+00 None	1.0E-03	None	None	None	2.5E-04 2.5E-02	None	None	1.0E-03	None	None	N/A	1.4E-03 1.4E-01	0.9E-03 N/A
Diazinon	N	1.7E-01	1.7E-01	None	None	4.3E-02	4.3E-02	None	1.7E-01	1.7E-01	None	None	2.3E-01	2.3E-01	N/A
Dibenz(a,h)anthracene	Υ	None	None	3.8E-02	1.8E-01	None	None	1.8E-02	None	None	3.8E-02	1.8E-01	N/A	N/A	5.7E-01
1,2-Dichlorobenzene	N	None	None	4.2E+02	1.3E+03	None	None	1.3E+02	None	None	4.2E+02	1.3E+03	N/A	N/A	2.4E+03
1,3-Dichlorobenzene	N	None	None	3.2E+02	9.6E+02	None	None	9.6E+01	None	None	3.2E+02	9.6E+02	N/A	N/A	1.8E+03
1,4-Dichlorobenzene	N	None	None	6.3E+01	1.9E+02	None	None	1.9E+01	None	None	6.3E+01	1.9E+02	N/A	N/A	3.5E+02
3,3-Dichlorobenzidine	Υ	None	None	2.1E-01	2.8E-01	None	None	2.8E-02	None	None	2.1E-01	2.8E-01	N/A	N/A	8.8E-01
Dichlorobromomethane	Y	None	None	5.5E+00	1.7E+02	None	None	1.7E+01	None	None	5.5E+00	1.7E+02	N/A	N/A	5.4E+02
1,2-Dichloroethane	Υ	None	None	3.8E+00	3.7E+02	None	None	3.7E+01	None	None	3.8E+00	3.7E+02	N/A	N/A	1.2E+03
1,1-Dichloroethylene	N	None	None	3.3E+02	7.1E+03	None	None	7.1E+02	None	None	3.3E+02	7.1E+03	N/A	N/A	1.3E+04 1.8E+04
1,2-trans-dichloroethylene 2,4-Dichlorophenol	N N	None None	None None	1.4E+02 7.7E+01	1.0E+04 2.9E+02	None None	None None	1.0E+03 2.9E+01	None None	None None	1.4E+02 7.7E+01	1.0E+04 2.9E+02	N/A N/A	N/A N/A	5.3E+04
2,4-Dichlorophenoxy Acetic	N	None	None	1.0E+02	None	None	None	None	None	None	1.0E+02	None	N/A	N/A	0.3L+02 N/A
1,2-Dichloropropane	Υ	None	None	5.0E+00	1.5E+02	None	None	1.5E+01	None	None	5.0E+00	1.5E+02	N/A	N/A	4.7E+02
1,3-Dichloropropene	Υ	None	None	3.4E+00	2.1E+02	None	None	2.1E+01	None	None	3.4E+00	2.1E+02	N/A	N/A	6.6E+02
Dieldrin	Υ	2.4E-01	5.6E-02	5.2E-04	5.4E-04	6.0E-02	1.4E-02	5.4E-05	2.4E-01	5.6E-02	5.2E-04	5.4E-04	3.2E-01	7.7E-02	1.7E-03
Diethyl Phthalate	N	None	None	1.7E+04	4.4E+04	None	None	4.4E+03	None	None	1.7E+04	4.4E+04	N/A	N/A	8.1E+04
2,4 Dimethylphenol	N	None	None	3.8E+02	8.5E+02	None	None	8.5E+01	None	None	3.8E+02	8.5E+02	N/A	N/A	1.6E+03
Dimethyl Phthalate	N	None	None	2.7E+05	1.1E+06	None	None	1.1E+05	None	None	2.7E+05	1.1E+06	N/A	N/A	2.0E+06
Di-n-Butyl Phthalate	N	None	None	2.0E+03	4.5E+03	None	None	4.5E+02	None	None	2.0E+03	4.5E+03	N/A	N/A	8.3E+03
2,4 Dinitrophenol 2-Methyl-4,6-Dinitrophenol	N N	None None	None None	6.9E+01 1.3E+01	5.3E+03 2.8E+02	None None	None None	5.3E+02 2.8E+01	None None	None None	6.9E+01 1.3E+01	5.3E+03 2.8E+02	N/A N/A	N/A N/A	9.8E+03 5.2E+02
2,4-Dinitrotoluene	Y	None	None	1.1E+00	3.4E+01	None	None	3.4E+00	None	None	1.1E+00	3.4E+01	N/A	N/A	1.1E+02
Dioxin+	N	None	None	5.0E-08	5.1E-08	None	None	5.1E-09	None	None	5.0E-08	5.1E-08	N/A	N/A	9.4E-08
1,2-Diphenylhydrazine	Υ	None	None	3.6E-01	2.0E+00	None	None	2.0E-01	None	None	3.6E-01	2.0E+00	N/A	N/A	6.3E+00
Alpha-Endosulfan	N	2.2E-01	5.6E-02	6.2E+01	8.9E+01	5.5E-02	1.4E-02	8.9E+00	2.2E-01	5.6E-02	6.2E+01	8.9E+01	2.9E-01	7.7E-02	1.6E+02
Beta-Endosulfan	N	2.2E-01	5.6E-02	6.2E+01	8.9E+01	5.5E-02	1.4E-02	8.9E+00	2.2E-01	5.6E-02	6.2E+01	8.9E+01	2.9E-01	7.7E-02	1.6E+02
Alpha+Beta-Endosulfan	N	2.2E-01	5.6E-02	None	None	5.5E-02	1.4E-02	None	2.2E-01	5.6E-02	None	None	2.9E-01	7.7E-02	N/A
Endosulfan Sulfate	N	None	None	6.2E+01	8.9E+01	None	None	8.9E+00	None	None	6.2E+01	8.9E+01	N/A	N/A	1.6E+02
Endrin Endrin Aldehyde	N N	8.6E-02 None	3.6E-02 None	5.9E-02 2.9E-01	6.0E-02 3.0E-01	2.2E-02 None	9.0E-03 None	6.0E-03 3.0E-02	8.6E-02 None	3.6E-02 None	5.9E-02 2.9E-01	6.0E-02 3.0E-01	1.1E-01 N/A	5.0E-02 N/A	1.1E-01 5.5E-01
Ethylbenzene	N	None	None	5.3E+02	2.1E+03	None	None	2.1E+02	None	None	5.3E+02	2.1E+03	N/A	N/A	3.9E+03
Fluoranthene	N	None	None	1.3E+02	1.4E+02	None	None	1.4E+01	None	None	1.3E+02	1.4E+02	N/A	N/A	2.6E+02
Fluorene	N	None	None	1.1E+03	5.3E+03	None	None	5.3E+02	None	None	1.1E+03	5.3E+03	N/A	N/A	9.8E+03
Foaming Agents (MBAS)	N	None	None	5.0E+02	None	None	None	None	None	None	5.0E+02	None	N/A	N/A	N/A
Guthion	N	None	1.0E-02	None	None	None	2.5E-03	None	None	1.0E-02	None	None	N/A	1.4E-02	N/A
Heptachlor	Υ	5.2E-01	3.8E-03	7.9E-04	7.9E-04	1.3E-01	9.5E-04	7.9E-05	5.2E-01	3.8E-03	7.9E-04	7.9E-04	6.9E-01	5.2E-03	2.5E-03
Heptachlor Epoxide	Y	5.2E-01	3.8E-03	3.9E-04	3.9E-04	1.3E-01	9.5E-04	3.9E-05	5.2E-01	3.8E-03	3.9E-04	3.9E-04	6.9E-01	5.2E-03	1.2E-03
Hexachlorobenzene Hexachlorobutadiene	Y Y	None None	None None	2.8E-03 4.4E+00	2.9E-03 1.8E+02	None None	None None	2.9E-04 1.8E+01	None None	None None	2.8E-03 4.4E+00	2.9E-03 1.8E+02	N/A N/A	N/A N/A	9.1E-03 5.7E+02
Hexachlorocyclohexane Alp	Y	None	None	2.6E-02	4.9E-02	None	None	4.9E-03	None	None	2.6E-02	4.9E-02	N/A	N/A	1.5E-01
Hexachlorocyclohexane Be	Y	None	None	9.1E-02	1.7E-01	None	None	1.7E-02	None	None	9.1E-02	1.7E-01	N/A	N/A	5.4E-01
Hexachlorocyclohexane Gamma-BHC (Lindane)	Υ	9.5E-01	None	9.8E-01	1.8E+00	2.4E-01	None	1.8E-01	9.5E-01	None	9.8E-01	1.8E+00	1.3E+00	N/A	5.7E+00
Hexachlorocyclopentadiene	N	None	None	4.0E+01	1.1E+03	None	None	1.1E+02	None	None	4.0E+01	1.1E+03	N/A	N/A	2.0E+03
Hexachloroethane	Υ	None	None	1.4E+01	3.3E+01	None	None	3.3E+00	None	None	1.4E+01	3.3E+01	N/A	N/A	1.0E+02
Hydrogen Sulfide	N	None	2.0E+00	None	None	None	5.0E-01	None	None	2.0E+00	None	None	N/A	2.8E+00	N/A
Indeno(1,2,3-cd)pyrene	Υ	None	None	3.8E-02	1.8E-01	None	None	1.8E-02	None	None	3.8E-02	1.8E-01	N/A	N/A	5.7E-01
Iron	N	None	None	3.0E+02	None	None	None	None	None	None	3.0E+02	None	N/A	N/A	N/A
Isophorone	Y	None	None	3.5E+02	9.6E+03	None	None	9.6E+02	None	None	3.5E+02	9.6E+03	N/A	N/A Zoro	3.0E+04
Kepone Lead	N N	None 1.1E+02	Zero 1.2E+01	None 1.5E+01	None None	None 2.7E+01	Zero 3.0E+00	None None	None 1.1E+02	Zero 1.2E+01	None 1.5E+01	None None	N/A 1.4E+02	Zero 1.6E+01	N/A N/A
Malathion	N N	None	1.2E+01 1.0E-01	None	None	None	3.0E+00 2.5E-02	None	None	1.2E+01 1.0E-01	None	None	1.4E+02 N/A	1.6E+01 1.4E-01	N/A N/A
Manganese	N	None	None	5.0E+01	None	None	None	None	None	None	5.0E+01	None	N/A	N/A	N/A
Mercury	N	1.4E+00	7.7E-01	None	None	3.5E-01	1.9E-01	None	1.4E+00	7.7E-01	None	None	1.9E+00	1.1E+00	N/A
Methyl Bromide	N	None	None	4.7E+01	1.5E+03	None	None	1.5E+02	None	None	4.7E+01	1.5E+03	N/A	N/A	2.8E+03
Methylene Chloride	Υ	None	None	4.6E+01	5.9E+03	None	None	5.9E+02	None	None	4.6E+01	5.9E+03	N/A	N/A	1.9E+04
Methoxychlor	N	None	3.0E-02	1.0E+02	None	None	7.5E-03	None	None	3.0E-02	1.0E+02	None	N/A	4.1E-02	N/A
Mirex	N	None	Zero	None	None	None	Zero	None	None	Zero	None	None	N/A	Zero	N/A

Nickel	N	1.7E+02	1.9E+01	6.1E+02	4.6E+03	4.2E+01	4.7E+00	4.6E+02	1.7E+02	1.9E+01	6.1E+02	4.6E+03	2.3E+02	2.6E+01	8.5E+03
Nitrate (as N)	N	None	None	1.0E+01 n	4.6E+03 None	None	None	None	None	None	1.0E+01 m		2.3E+02 N/A	2.6E+01 N/A	0.5E+03 N/A
Nitrobenzene	N	None	None	1.7E+01	6.9E+02	None	None	6.9E+01	None	None	1.7E+01	6.9E+02	N/A	N/A	1.3E+03
N-Nitrosodimethylamine	Y	None	None	6.9E-03	3.0E+01	None	None	3.0E+00	None	None	6.9E-03	3.0E+01	N/A N/A	N/A	9.5E+01
N-Nitrosodiphenylamine	Ϋ́	None	None	3.3E+01	6.0E+01	None	None	6.0E+00	None	None	3.3E+01	6.0E+01	N/A	N/A	1.9E+02
N-Nitrosodipnenylamine N-Nitrosodi-n-propylamine	Ϋ́	None	None	5.0E-02	5.1E+00	None	None	5.1E-01	None	None	5.0E-02	5.1E+00	N/A N/A	N/A N/A	1.9E+02 1.6E+01
Nonylphenol	N	2.8E+01	6.6E+00	None	None	7.0E+00	1.7E+00	None	2.8E+01	6.6E+00	None	None	3.7E+01	9.1E+00	N/A
Parathion	N	6.5E-02	1.3E-02	None	None	1.6E-02	3.3E-03	None	6.5E-02	1.3E-02	None	None	8.6E-02	1.8E-02	N/A
Paratnion PCB Total	Y	None	1.3E-02 1.4E-02	6.4E-04	6.4E-04	None	3.5E-03	6.4E-05	None	1.3E-02 1.4E-02	6.4E-04	6.4E-04	8.6E-02 N/A	1.8E-02 1.9E-02	2.0E-03
	Y														
Pentachlorophenol	Y N	7.1E+00	5.3E+00	2.7E+00	3.0E+01 8.6E+05	1.8E+00	1.3E+00	3.0E+00 8.6E+04	7.1E+00	5.3E+00	2.7E+00 1.0E+04	3.0E+01	9.4E+00 N/A	7.2E+00	9.5E+01 1.6E+06
Phenol		None	None	1.0E+04		None	None		None	None		8.6E+05		N/A	
Pyrene	N	None	None	8.3E+02	4.0E+03	None	None	4.0E+02	None	None	8.3E+02	4.0E+03	N/A	N/A	7.4E+03
RadNuc - Beta Part & Phote	N	None	None	4.0E+00 n	None	None	None	None	None	None	4.0E+00 m			N/A	7.4E+00
RadNuc - Gross Alpha Part	N	None	None	1.5E+01 p	None	None	None	None	None	None	1.5E+01 p		N/A	N/A	N/A
RadNuc - Radium 226 + 228	N	None	None	5.0E+00 p	None	None	None	None	None	None	5.0E+00 p		N/A	N/A	N/A
RadNuc - Uranium	N	None	None	3.0E+01	None	None	None	None	None	None	3.0E+01	None	N/A	N/A	N/A
Selenium, Total Recoverable	N	2.0E+01	5.0E+00	1.7E+02	4.2E+03	5.0E+00	1.3E+00	4.2E+02	2.0E+01	5.0E+00	1.7E+02	4.2E+03	2.7E+01	6.9E+00	7.7E+03
Silver	N	3.0E+00	None	None	None	7.5E-01	None	None	3.0E+00	None	None	None	4.0E+00	N/A	N/A
Sulfate	N	None	None	2.5E+02 n	None	None	None	None	None	None	2.5E+02 m		N/A	N/A	N/A
1,1,2,2-Tetrachloroethane	Υ	None	None	1.7E+00	4.0E+01	None	None	4.0E+00	None	None	1.7E+00	4.0E+01	N/A	N/A	1.3E+02
Tetrachloroethylene	Υ	None	None	6.9E+00	3.3E+01	None	None	3.3E+00		None	6.9E+00	3.3E+01	0.0E+00	N/A	1.0E+02
Thallium	N	None	None	2.4E-01	4.7E-01	None	None	4.7E-02	None	None	2.4E-01	4.7E-01	N/A	N/A	8.7E-01
Toluene	N	None	None	5.1E+02	6.0E+03	None	None	6.0E+02	None	None	5.1E+02	6.0E+03	N/A	N/A	1.1E+04
Total Dissolved Solids	N	None	None	5.0E+05	None	None	None	None	None	None	5.0E+05	None	N/A	N/A	N/A
Toxaphene	Υ	7.3E-01	2.0E-04	2.8E-03	2.8E-03	1.8E-01	5.0E-05	2.8E-04	7.3E-01	2.0E-04	2.8E-03	2.8E-03	9.7E-01	2.8E-04	8.8E-03
Tributyltin	N	4.6E-01	7.2E-02	None	None	1.2E-01	1.8E-02	None	4.6E-01	7.2E-02	None	None	6.1E-01	9.9E-02	N/A
1,2,4-Trichlorobenzene	N	None	None	3.5E+01	7.0E+01	None	None	7.0E+00	None	None	3.5E+01	7.0E+01	N/A	N/A	1.3E+02
1,1,2-Trichloroethane	Υ	None	None	5.9E+00	1.6E+02	None	None	1.6E+01	None	None	5.9E+00	1.6E+02	N/A	N/A	5.0E+02
Trichloroethylene	Υ	None	None	2.5E+01	3.0E+02	None	None	3.0E+01	None	None	2.5E+01	3.0E+02	N/A	N/A	9.5E+02
2,4,6-Trichlorophenol	Υ	None	None	1.4E+01	2.4E+01	None	None	2.4E+00	None	None	1.4E+01	2.4E+01	N/A	N/A	7.6E+01
2-(2,4,5-Trichlorophenoxy propionic acid (Silvex)	N	None	None	5.0E+01	None	None	None	None	None	None	5.0E+01	None	N/A	N/A	N/A
Vinyl Chloride	Υ	None	None	2.5E-01	2.4E+01	None	None	2.4E+00	None	None	2.5E-01	2.4E+01	N/A	N/A	7.6E+01
Zinc	N	1.1E+02	1.1E+02	7.4E+03	2.6E+04	2.7E+01	2.7E+01	2.6E+03	1.1E+02	1.1E+02	7.4E+03	2.6E+04	1.4E+02	1.5E+02	4.8E+04

#### PROTOCOL FOR THE EVALUATION OF THE EFFLUENT – TOXIC POLLUTANTS

Toxic pollutants were evaluated in accordance with OWP Guidance Memo No. 00-2011. Acute and Chronic WLAs (WLAa and WLAc) were analyzed according to the protocol below using a statistical approach (STAT.exe) to determine the necessity and magnitude of limits. Human Health WLAs (WLAhh) were analyzed according to the same protocol through a simple comparison with the effluent data. If the WLAhh exceeded the effluent datum or data mean, no limits were required. If the effluent datum or data mean exceeded the WLAhh, the WLAhh was imposed as the limit. Since there are no data available immediately upstream of this discharge, all other upstream (background) pollutant concentrations are assumed to be "0".

The steps used in evaluating the effluent data are as follows:

- A. If all data are reported as "below detection" or < the required Quantification Level (QL), and at least one detection level is = the required QL, then the pollutant is considered to be not significantly present in the discharge and no further monitoring is required.
- B. If all data are reported as "below detection", and all detection levels are > the required QL, then an evaluation is performed in which the pollutant is assumed present at the lowest reported detection level.
  - B.1. If the evaluation indicates that no limits are needed, then the existing data set is adequate and no further monitoring is required.
  - B.2. If the evaluation indicates that limits are needed, then the existing data set is inadequate to make a determination and additional monitoring is required.
- C. If any data value is reported as detectable at or above the required QL, then the data are adequate to determine whether effluent limits are needed.
  - C.1. If the evaluation indicates that no limits are needed, then no further monitoring is required.
  - C.2. If the evaluation indicates that limits are needed, then the limits and associated requirements are specified in the draft permit.
  - C.3. If the evaluation indicates that limits are needed, but the metals data are reported as a form other than "Dissolved", then the existing data set is inadequate to make a determination and additional monitoring is required.

## TOXLARGE - 0.099 MGD

Parameter	CASRN	QL (ug/L)	Data (ug/L unless noted otherwise)	Source of Data	Data Eval (all flow tiers)
		Ml	ETALS		
Antimony, dissolved	7440-36-0	0.2	<5.0	a	B.1
Arsenic, dissolved	7440-38-2	1.0	<5.0	a	B.1
Barium, dissolved	7440-39-3		Applicable to PWS waters only		
Cadmium, dissolved	7440-43-9	0.3	0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	b,c	A
Chromium III, dissolved	16065-83-1	0.5	<5.0	a	B.1
Chromium VI, dissolved	18540-29-9	0.5	<0.01	a	A
Chromium, Total	7440-47-3		Applicable to PWS waters only		
Copper, dissolved	7440-50-8	0.5	8.7, 9, 14, 12, 0.005, 13, 11, 10, 9, 14, 12, 8, 10, 12, 18, 10, 9, 13, 9, 9, 18, 11, 27, 8.3, 7.8, 9, 8, 9, 9, 17, 10, 12, 9, 139, 17, 18, 18, 12, 21, 44, 28, 14, 21, 18, 19, 28, 22, 15, 17, 13, 15, 8.1, 28, 13, 13, 16, 14, 19, 25	b,c	C.2
Iron, dissolved	7439-89-6	1.0	Applicable to PWS waters only		
Lead, dissolved	7439-92-1	0.5	<5.0	a	B.1
Manganese, dissolved	7439-96-5	0.2	Applicable to PWS waters only		
Mercury, dissolved	7439-97-6	1.0	<0.20	a	A
Nickel, dissolved	7440-02-0	0.5	<5.0	a	B.1
Selenium, total recoverable	7782-49-2	2.0	<5.0	a	B.2
Silver, dissolved	7440-22-4	0.2	<5.0	a	B.2
Thallium, dissolved	7440-28-0		<2	a	A
Zinc, dissolved	7440-66-6	2.0	230.9, 51	a,c	C.2
	PI	ESTIC	IDES/PCBS		
Aldrin <sup>C</sup>	309-00-2	0.05	<0.05	a	A
Chlordane <sup>C</sup>	57-74-9	0.2	<0.05	a	A
Chlorpyrifos	2921-88-2	(5)	<1	a	B.1
DDD <sup>C</sup>	72-54-8	0.1	< 0.05	a	A
DDE <sup>C</sup>	72-55-9	0.1	< 0.05	a	A
DDT <sup>C</sup>	50-29-3	0.1	< 0.05	a	A
Demeton	8065-48-3		<2	a	B.1
Diazinon	333-41-5		NEW REQUIREMENT. Needs to be sampled.		
2,4-Dichlorophenoxy acetic acid (synonym = 2,4-D)	94-75-7		Applicable to PWS waters only		
Dieldrin <sup>C</sup>	60-57-1	0.1	<0.05	a	A
Alpha-Endosulfan	959-98-8	0.1	<0.05	a	A
Beta-Endosulfan	33213-65-9	0.1	<0.05	a	A
Alpha-Endosulfan + Beta-Endosulfan			<0.05	a	A
Endosulfan Sulfate	1031-07-8	0.1	<0.05	a	A
Endrin	72-20-8	0.1	< 0.05	a	A

Fact Sheet - VPDES Permit No. VA0024147 - Fork Union Military Academy STP

Parameter	CASRN	QL (ug/L)	Data (ug/L unless noted otherwise)	Source of Data	Data Eval (all flow tiers)
Endrin Aldehyde	7421-93-4		<0.05	a	A
Guthion	86-50-0		<1.0 mg/L	a	A
Heptachlor <sup>C</sup>	76-44-8	0.05	< 0.05	a	A
Heptachlor Epoxide <sup>C</sup>	1024-57-3		< 0.05	a	A
Hexachlorocyclohexane Alpha-BHC <sup>C</sup>	319-84-6		< 0.05	a	A
Hexachlorocyclohexane Beta-BHC C	319-85-7		< 0.05	a	A
Hexachlorocyclohexane Gamma-BHC (synonym = Lindane)	58-89-9		<0.05	a	A
Kepone	143-50-0		<10.0	a	A
Malathion	121-75-5		<1.0 mg/L	a	A
Methoxychlor	72-43-5		<0.15	a	A
Mirex	2385-85-5		<0.15	a	A
Parathion	56-38-2		<2.0	a	A
PCB Total <sup>C</sup>	1336-36-3	7.0	< 0.05	a	A
Toxaphene <sup>C</sup>	8001-35-2	5.0	<0.5	a	A
2-(2,4,5-Trichlorophenoxy) propionic acid (synonym = Silvex)	93-72-1		Applicable to PWS waters only		
Tributyltin	60-10-5		< 0.01	a	A
Вл	ASE NE	UTRA	L EXTRACTABLES		
Acenaphthene	83-32-9	10.0	<5.0	a	A
Anthracene	120-12-7	10.0	<5.0	a	A
Benzidine <sup>C</sup>	92-87-5		<50	a	A
Benzo (a) anthracene <sup>C</sup>	56-55-3	10.0	<5.0	a	A
Benzo (b) fluoranthene <sup>C</sup>	205-99-2	10.0	<5.0	a	A
Benzo (k) fluoranthene <sup>C</sup>	207-08-9	10.0	<5.0	a	A
Benzo (a) pyrene <sup>C</sup>	50-32-8	10.0	<5.0	a	A
Bis 2-Chloroethyl Ether <sup>C</sup>	111-44-4		<5.0	a	A
Bis 2-Chloroisopropyl Ether	108-60-1		<5.0	a	A
Bis-2-Ethylhexyl Phthalate <sup>C</sup>	117-81-7	10.0	<15.0	a	B.1
Butyl benzyl phthalate	85-68-7	10.0	<5.0	a	A
2-Chloronaphthalene	91-58-7		<5.0	a	A
Chrysene <sup>C</sup>	218-01-9	10.0	<5.0	a	A
Dibenz(a,h)anthracene <sup>C</sup>	53-70-3	20.0	<5.0	a	A
1,2-Dichlorobenzene	95-50-1	10.0	<5.0	a	A
1,3-Dichlorobenzene	541-73-1	10.0	<5.0	a	A
1,4-Dichlorobenzene	106-46-7	10.0	<5.0	a	A
3,3-Dichlorobenzidine <sup>C</sup>	91-94-1		<25	a	A
Diethyl phthalate	84-66-2	10.0	<5.0	a	A
Dimethyl phthalate	131-11-3		<5.0	a	A
Di-n-Butyl Phthalate	84-74-2	10.0	<5.0	a	A
2,4-Dinitrotoluene	121-14-2	10.0	<5.0	a	A
1,2-Diphenylhydrazine <sup>C</sup>	122-66-7		<5.0	a	A
Fluoranthene	206-44-0	10.0	<5.0	a	A
Fluorene	86-73-7	10.0	<5.0	a	A
					-
Hexachlorobenzene <sup>C</sup>	118-74-1		<5.0	a	A

Fact Sheet - VPDES Permit No. VA0024147 - Fork Union Military Academy STP

Parameter	CASRN	QL (ug/L)	Data (ug/L unless noted otherwise)	Source of Data	Data Eval (all flow tiers)
Hexachlorobutadiene <sup>C</sup>	87-68-3		<5.0	a	A
Hexachlorocyclopentadiene	77-47-4		<10.0	a	A
Hexachloroethane <sup>C</sup>	67-72-1		<5.0	a	A
Indeno(1,2,3-cd)pyrene <sup>C</sup>	193-39-5	20.0	<5.0	a	A
Isophorone <sup>C</sup>	78-59-1	10.0	<10.0	a	A
Nitrobenzene	98-95-3	10.0	<5.0	a	A
N-Nitrosodimethylamine <sup>C</sup>	62-75-9		<5.0	a	A
N-Nitrosodi-n-propylamine <sup>C</sup>	621-64-7		<5.0	a	A
N-Nitrosodiphenylamine <sup>C</sup>	86-30-6		<10.0	a	A
Pyrene	129-00-0	10.0	<5.0	a	A
1,2,4-Trichlorobenzene	120-82-1	10.0	<5.0	a	A
	L	VOL	ATILES		L
Acrolein	107-02-8		<100	a	A
Acrylonitrile C	107-13-1		<100	a	A
Benzene <sup>C</sup>	71-43-2	10.0	<5.0	a	A
Bromoform <sup>C</sup>	75-25-2	10.0	<5.0	a	A
Carbon Tetrachloride <sup>C</sup>	56-23-5	10.0	<5.0	a	A
Chlorobenzene	108-90-7	50.0	<5.0	a	A
Chlorodibromomethane <sup>C</sup>	124-48-1	10.0	<5.0	a	A
Chloroform	67-66-3	10.0	<5.0	a	A
Dichlorobromomethane <sup>C</sup>	75-27-4	10.0	<5.0	a	A
1,2-Dichloroethane <sup>C</sup>	107-06-2	10.0	<5.0	a	A
1,1-Dichloroethylene	75-35-4	10.0	<5.0	a	A
1,2-trans-dichloroethylene	156-60-5		<5.0	a	A
1,2-Dichloropropane <sup>C</sup>	78-87-5		<5.0	a	A
1,3-Dichloropropene <sup>C</sup>	542-75-6		<5.0	a	A
Ethylbenzene	100-41-4	10.0	<5.0	a	A
Methyl Bromide	74-83-9		<10.0	a	A
Methylene Chloride <sup>C</sup>	75-09-2	20.0	<5.0	a	A
1,1,2,2-Tetrachloroethane <sup>C</sup>	79-34-5		<5.0	a	A
Tetrachloroethylene	127-18-4	10.0	<5.0	a	A
Toluene	10-88-3	10.0	<5.0	a	A
1,1,2-Trichloroethane <sup>C</sup>	79-00-5		<5.0	a	A
Trichloroethylene <sup>C</sup>	79-01-6	10.0	<5.0	a	A
Vinyl Chloride <sup>C</sup>	75-01-4	10.0	<5.0	a	A
	R	ADIO	NUCLIDES		
Beta Particle & Photon Activity (mrem/yr)	N/A		Applicable to PWS waters only		
Combined Radium 226 and 228 (pCi/L)	N/A		Applicable to PWS waters only		
Gross Alpha Particle Activity (pCi/L)	N/A		Applicable to PWS waters only		
Uranium	N/A		Applicable to PWS waters only		
	ACI	D EXT	TRACTABLES		
2-Chlorophenol	95-57-8	10.0	<5.0	a	A
2,4-Dichlorophenol	120-83-2	10.0	<5.0	a	A

Fact Sheet – VPDES Permit No. VA0024147 – Fork Union Military Academy STP

Parameter	CASRN	QL (ug/L)	Data (ug/L unless noted otherwise)	Source of Data	Data Eval (all flow tiers)
2,4-Dimethylphenol	105-67-9	10.0	<5.0	a	A
2,4-Dinitrophenol	51-28-5		<5.0	a	A
2-Methyl-4,6-Dinitrophenol	534-52-1		<5.0	a	A
Nonylphenol	104-40-51		NEW REQUIREMENT. Needs to be sampled.		
Pentachlorophenol <sup>C</sup>	87-86-5	50.0	<25.0	a	A
Phenol	108-95-2	10.0	<5.0	a	A
2,4,6-Trichlorophenol <sup>C</sup>	88-06-2	10.0	<10.0	a	A
MISCELLANEOUS					
Ammonia-N (mg/L) (Jun-Nov)	766-41-7	0.2 mg/L	Default = 9 mg/L	d	C.2
Ammonia-N (mg/L) (Dec-May)	766-41-7	0.2 mg/L	Default = 9 mg/L	d	C.2
Chloride (mg/L)	16887-00-6		69.7 mg/L	a	C.1
TRC (mg/L)	7782-50-5	0.1 mg/L	Default = 20 mg/L	d	C.2
Cyanide, Free	57-12-5	10.0	<0.005 mg/L	a	A
Dioxin (2,3,7,8-tetrachlorodibenzo-p-dioxin)	1746-01-6	0.01	Applicable to Paper Mills & Oil Refineries only		
Foaming Agents (as MBAS)	N/A		Applicable to PWS waters only		
Hydrogen Sulfide	7783-06-4		<1 mg/L	a	A
Nitrate as N (mg/L)	14797-55-8		Applicable to PWS waters only		
Sulfate (mg/L)	N/A		Applicable to PWS waters only		
Total Dissolved Solids (mg/L)	N/A		Applicable to PWS waters only		

## "Type" column indicates a category assigned to the referenced substance (see below):

A = Acid Extractable Organic Compounds

B = Base/Neutral Extractable Organic Compounds

M = Metals

p = PCBs

P = Pesticides

R = Radionuclides

V = Volatile Organic Compounds

X = Miscellaneous Compounds and Parameters

The **superscript "C"** following the parameter name indicates that the substance is a known or suspected carcinogen; human health criteria at risk level  $10^{-5}$ .

#### "Source of Data" codes:

a = permittee monitoring performed in December 2011

b = data submitted on DMR

c = permittee monitoring data performed 2002

d = default effluent concentration

#### "Data Evaluation" codes:

See section titled PROTOCOL FOR THE EVALUATION OF EFFLUENT TOXIC POLLUTANTS for an explanation of the code used.

**CASRN** = Chemical Abstract Service Registry Number for each parameter is referenced in the current Water Quality Standards. A unique numeric identifier designating only one substance. The Chemical Abstract Service is a division of the American Chemical Societ y.

## STAT.EXE RESULTS – 0.06 MGD:

Ammonia-N Wet Chronic averaging period = 30 WLAa = 47 WLAc = 17 Q.L. = 0.2 # samples/mo. = 1 # samples/wk. = 1  Summary of Statistics: # observations = 1 Expected Value = 9 Variance = 29 16	Cadmium, Dissolved Chemical = Cadmium, Dissolved Chronic averaging period = 4 WLAa = 5.1 WLAc = 1.6 Q.L. = 0.3 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 91 Expected Value = .316409
C.V. = 0.6  97th percentile daily values = 21.9007  97th percentile 4 day average = 14.9741  97th percentile 30 day average= 10.8544  # < Q.L. = 0  Model used = BPJ Assumptions, type 2 data  No Limit is required for this material  The data are: 9	Variance = .005238 C.V. = 0.228737 97th percentile daily values = .471688 97th percentile 4 day average = .389540 97th percentile 30 day average= .341264 # <q.l. 0="" =="" for="" is="" limit="" material<="" model="" no="" required="" td="" this="" used="lognormal"></q.l.>
	The data are: 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,
TRC Chronic averaging period = 4 WLAa = 0.029 WLAc = 0.018 Q.L. = 0.1 # samples/mo. = 30 # samples/wk. = 7	Zinc, Dissolved Chronic averaging period = 4 WLAa = 160 WLAc = 170 Q.L. = 2.0 # samples/mo. = 1 # samples/wk. = 1
Summary of Statistics: # observations = 1 Expected Value = 20 Variance = 144 C.V. = 0.6 97th percentile daily values = 48.6683 97th percentile 4 day average = 33.2758 97th percentile 30 day average = 24.1210 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data	Summary of Statistics: # observations = 2 Expected Value = 140.95 Variance = 7152.08 C.V. = 0.6 97th percentile daily values = 342.990 97th percentile 4 day average = 234.511 97th percentile 30 day average= 169.993 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data
A limit is needed based on Chronic Toxicity Maximum Daily Limit = 2.63263461129582E-02 Average Weekly Limit = 1.60776892986318E-0 Average Monthly Limit = 1.30478943008877E-02 The data are: 20	A limit is needed based on Acute Toxicity Maximum Daily Limit = 160 Average Weekly Limit = 160 Average Monthly Limit = 160 The data are: 230.9, 51
	Chronic averaging period = 30 WLAa = 47 WLAc = 17 Q.L. = 0.2 # samples/mo. = 1 # samples/wk. = 1  Summary of Statistics: # observations = 1 Expected Value = 9 Variance = 29.16 C.V. = 0.6 97th percentile daily values = 21.9007 97th percentile 4 day average = 14.9741 97th percentile 30 day average= 10.8544 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data  No Limit is required for this material The data are: 9  Expected Value = 20 Variance = 144 C.V. = 0.6 97th percentile daily values = 48.6683 97th percentile daily values = 48.6683 97th percentile daily values = 48.6683 97th percentile daily values = 24.1210 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data  A limit is needed based on Chronic Toxicity Maximum Daily Limit = 2.63263461129582E-02 Average Weekly Limit = 1.60776892986318E-0 Average Monthly Limit = 1.30478943008877E-02

## STAT.EXE RESULTS – 0.075 MGD:

r	T	
Ammonia-N Annual	Ammonia-N Wet	TRC
Chronic averaging period = 30	Chronic averaging period = 30	Chronic averaging period = 4
WLAa = 16	WLAa = 39	WLAa = 0.027
WLAc = 2.9	WLAc = 14	WLAc = 0.016
O.L. = 0.2	O.L. = 0.2	O.L. = 0.1
~		
# samples/mo. = 1	# samples/mo. = 1	# samples/mo. = 30
# samples/wk. = 1	# samples/wk. = 1	# samples/wk. = 7
		-
Summary of Statistics:	Summary of Statistics:	Summary of Statistics:
# observations = 1	# observations = 1	# observations = 1
Expected Value = 9	Expected Value = 9	Expected Value = 20
Variance = 29.16	Variance = 29.16	Variance = 144
C.V. = 0.6	C.V. = 0.6	C.V. = 0.6
97th percentile daily values = 21.9007	97th percentile daily values = 21.9007	97th percentile daily values = 48.6683
97th percentile 4 day average = 14.9741	97th percentile 4 day average = 14.9741	97th percentile 4 day average = 33.2758
97th percentile 30 day average= 10.8544	97th percentile 30 day average= 10.8544	97th percentile 30 day average= 24.1210
# < Q.L. = 0	# < Q.L. = 0	# < Q.L. = 0
Model used = BPJ Assumptions, type 2 data	Model used = BPJ Assumptions, type 2 data	Model used = BPJ Assumptions, type 2 data
, ,, ,, ,,	, ,, ,, , , , , , , , , , , , , ,	
A limit is an adult band on Classic Tool is	No I imit is as assisted for this section.	A limit is another than the Character Transfer
A limit is needed based on Chronic Toxicity	No Limit is required for this material	A limit is needed based on Chronic Toxicity
Maximum Daily Limit = 5.8512432709073		Maximum Daily Limit = $2.34011965448517E-02$
Average Weekly Limit = $5.8512432709073$	The data are: 9	Average Weekly Limit = $1.42912793765616E-02$
Average Monthly Limit = 5.8512432709073		Average Monthly Limit = 1.15981282674557E-02
Tretage Figure 2102 12 1027 09072		11701age 17101am
The data area 0		The Jets 200
The data are: 9		The data are: 20
Cadmium, Dissolved	Copper, Dissolved	Zinc, Dissolved
Chronic averaging period = 4	Chronic averaging period = 4	Chronic averaging period = 4
WLAa = 4.9	WLAa = 17	WLAa = 150
WLAc = 1.5	WLAC = 12	WLAc = 160
Q.L. $= 0.3$	Q.L. $= 0.5$	Q.L. $= 2.0$
# samples/mo. = 1	# samples/mo. = 1	# samples/mo. = 1
# samples/wk. = 1	# samples/wk. = 1	# samples/wk. = 1
*	*	*
Cummary of Statistics	Cummary of Statistics	Cummour, of Statistica
Summary of Statistics:	Summary of Statistics:	Summary of Statistics:
# observations = 91	# observations = 59	# observations = 2
Expected Value = .316409	Expected Value = 15.7336	Expected Value = 140.95
Variance = .005238	Variance = 75.9638	Variance = 7152.08
C.V. = 0.228737	C.V. = 0.553953	C.V. = 0.6
97th percentile daily values = .471688	97th percentile daily values = 36.2364	97th percentile daily values = 342.990
97th percentile 4 day average = .389540	97th percentile 4 day average = 25.2857	97th percentile 4 day average = 234.511
97th percentile 30 day average = .341264	97th percentile 30 day average= 18.7268	97th percentile 30 day average= 169.993
# < Q.L. = 0	# < Q.L. = 1	# < Q.L. = 0
Model used = lognormal	Model used = delta lognormal	Model used = BPJ Assumptions, type 2 data
1410del doct — logilorinal	1710dei doct — deita logifolillai	moder asca — Dr. F. Assumptions, type 2 data
l	l	
No Limit is required for this material	A limit is needed based on Acute Toxicity	A limit is needed based on Acute Toxicity
	Maximum Daily Limit = 17	Maximum Daily Limit = 150
The data are: 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	Average Weekly Limit = 17	Average Weekly Limit $= 150$
	Average Monthly Limit = 17	Average Monthly Limit = 150
0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	Average Monthly Link = 17	Average Monuny Linit = 150
0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,		
0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	The data are: 8.7, 9, 14, 12, 0.005, 13, 11, 10, 9,	The data are: 230.9, 51
0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	14, 12, 8, 10,12, 18, 10, 9, 13, 9, 9, 18, 11,	
0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	27, 8.3, 7.8, 9, 8, 9, 9, 17, 10, 12, 9, 139, 17,	
0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	18, 18, 12, 21, 44, 28, 14, 21, 18, 19, 28, 22,	
0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	15, 17, 13, 15, 8.1, 28, 13, 13, 16, 14, 19, 25	
0.3, 0.3, 0.3, 0.3, 2.5, 0.45		

## STAT.EXE RESULTS – 0.099 MGD:

Ammonia-N Annual Chronic averaging period = 30 WLAa = 15 WLAc = 2.5 Q.L. = 0.2 # samples/mo. = 1 # samples/wk. = 1	Ammonia-N Wet Chronic averaging period = 30 WLAa = 32 WLAc = 11 Q.L. = 0.2 # samples/mo. = 1 # samples/wk. = 1	TRC Chronic averaging period = 4 WLAa = 0.025 WLAc = 0.015 Q.L. = 0.1 # samples/mo. = 30 # samples/wk. = 7
Summary of Statistics: # observations = 1 Expected Value = 9 Variance = 29.16 C.V. = 0.6 97th percentile daily values = 21.9007 97th percentile 4 day average = 14.9741 97th percentile 30 day average = 10.8544 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data	Summary of Statistics: # observations = 1  Expected Value = 9  Variance = 29.16  C.V. = 0.6  97th percentile daily values = 21.9007  97th percentile 4 day average = 14.9741  97th percentile 30 day average = 10.8544  # < Q.L. = 0  Model used = BPJ Assumptions, type 2 data	Summary of Statistics: # observations = 1  Expected Value = 20  Variance = 144  C.V. = 0.6  97th percentile daily values = 48.6683  97th percentile 4 day average = 33.2758  97th percentile 30 day average = 24.1210 # < Q.L. = 0  Model used = BPJ Assumptions, type 2 data
A limit is needed based on Chronic Toxicity Maximum Daily Limit = 5.04417523354078 Average Weekly Limit = 5.04417523354078 Average Monthly Limit = 5.04417523354078	No Limit is required for this material The data are: 9	A limit is needed based on Chronic Toxicity  Maximum Daily Limit = 2.19386217607985E-02  Average Weekly Limit = 1.33980744155265E-02  Average Monthly Limit = 1.08732452507397E-02
The data are: 9  Cadmium, Dissolved Chronic averaging period = 4  WLAa = 4.7  WLAc = 1.4  Q.L. = 0.3  # samples/mo. = 1  # samples/wk. = 1	Copper, Dissolved Chronic averaging period = 4 WLAa = 16 WLAc = 11 Q.L. = 0.5 # samples/mo. = 1 # samples/wk. = 1	The data are: 20  Zinc, Dissolved Chronic averaging period = 4  WLAa = 140  WLAc = 150  Q.L. = 2.0  # samples/mo. = 1 # samples/wk. = 1
Summary of Statistics: # observations = 91 Expected Value = .316409 Variance = .005238 C.V. = 0.228737 97th percentile daily values = .471688 97th percentile 4 day average = .389540 97th percentile 30 day average = .341264 # < Q.L. = 0 Model used = lognormal	Summary of Statistics: # observations = 59 Expected Value = 15.7336 Variance = 75.9638 C.V. = 0.553953 97th percentile daily values = 36.2364 97th percentile 4 day average = 25.2857 97th percentile 30 day average = 18.7268 # < Q.L. = 1 Model used = delta lognormal	Summary of Statistics: # observations = 2 Expected Value = 140.95 Variance = 7152.08 C.V. = 0.6 97th percentile daily values = 342.990 97th percentile 4 day average = 234.511 97th percentile 30 day average = 169.993 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data
No Limit is required for this material  The data are: 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3, 0.3,	A limit is needed based on Chronic Toxicity Maximum Daily Limit = 15.7638399830945 Average Weekly Limit = 15.7638399830945 Average Monthly Limit = 15.763839983094 The data are: 8.7, 9, 14, 12, 0.005, 13, 11, 10, 9, 14, 12, 8, 10, 12, 18, 10, 9, 13, 9, 9, 18, 11, 27, 8.3, 7.8, 9, 8, 9, 9, 17, 10, 12, 9, 139, 17, 18, 18, 12, 21, 44, 28, 14, 21, 18, 19, 28, 22, 15, 17, 13, 15, 8.1, 28, 13, 13, 16, 14, 19, 25	A limit is needed based on Acute Toxicity  Maximum Daily Limit = 140  Average Weekly Limit = 140  Average Monthly Limit = 140  The data are: 230.9, 51

Arsenic Chronic averaging period = 4 WLAa = 450 WLAc = 210 Q.L. = 1.0 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 1 Expected Value = 5 Variance = 9 C.V. = 0.6 97th percentile daily values = 12.1670 97th percentile 4 day average = 8.31895 97th percentile 30 day average = 6.03026 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data	Chloride Chronic averaging period = 4 WLAa = 1100 WLAc = 320 Q.L. = 1.0 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 1 Expected Value = 69.7 Variance = 1748.91 C.V. = 0.6 97th percentile daily values = 169.609 97th percentile 4 day average = 115.966 97th percentile 30 day average = 84.0619 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data	Chromium III, Dissolved Chronic averaging period = 4 WLAa = 700 WLAc = 94 Q.L. = 0.5 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 1 Expected Value = 5 Variance = 9 C.V. = 0.6 97th percentile daily values = 12.1670 97th percentile 4 day average = 8.31895 97th percentile 30 day average = 6.03026 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data
No Limit is required for this material	No Limit is required for this material	No Limit is required for this material
The data are: 5	The data are: 69.7	The data are: 5
Lead, Dissolved Chronic averaging period = 4 WLAa = 140 WLAc = 16 Q.L. = 0.5 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 1 Expected Value = 5 Variance = 9 C.V. = 0.6 97th percentile daily values = 12.1670 97th percentile 4 day average = 8.31895 97th percentile 30 day average = 6.03026 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data No Limit is required for this material The data are: 5	Nickel, Dissolved Chronic averaging period = 4 WLAa = 230 WLAc = 26 Q.L. = 0.5 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 1 Expected Value = 5 Variance = 9 C.V. = 0.6 97th percentile daily values = 12.1670 97th percentile 4 day average = 8.31895 97th percentile 30 day average = 6.03026 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data No Limit is required for this material The data are: 5	Selenium, Dissolved Chronic averaging period = 4 WLAa = 27 WLAc = 6.9 Q.L. = 2.0 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 1 Expected Value = 5 Variance = 9 C.V. = 0.6 97th percentile daily values = 12.1670 97th percentile 4 day average = 8.31895 97th percentile 30 day average = 6.03026 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data A limit is needed based on Chronic Toxicity Maximum Daily Limit = 10.0917660099673 Average Weekly Limit = 10.0917660099673 The data are: 5
Silver, Dissolved Chronic averaging period = 4 WLAa = 4 WLAc = Q.L. = 0.2 # samples/mo. = 1 # samples/wk. = 1 Summary of Statistics: # observations = 1 Expected Value = 5 Variance = 9 C.V. = 0.6 97th percentile daily values = 12.1670 97th percentile 4 day average = 8.31895 97th percentile 30 day average = 6.03026 # < Q.L. = 0 Model used = BPJ Assumptions, type 2 data A limit is needed based on Acute Toxicity Maximum Daily Limit = 4 Average Weekly Limit = 4 Average Monthly Limit = 4 The data are: 5		

#### BASES FOR PERMIT SPECIAL CONDITIONS

Tabulated below are the sections of the permit, with any changes and the reasons for the changes identified. Also provided is the basis for each of the permit special conditions.

Cover Page

• Content and format as prescribed by the VPDES Permit Manual.

#### Part I.A.1. Effluent Limitations and Monitoring Requirements:

*Updates Part I.A.1. of the previous permit with the following:* 

- Changes were made to the format and introductory language.
- More stringent Copper limits were included.
- More stringent TRC limits were included.
- The E. coli monitoring was increased to 2/Week.
- Zinc limits were added.
- Cadmium limits were removed.
- Ammonia-N (Dec-May) limits were removed.
- Ammonia-N (Jun-Nov) limits were included.
- TKN (Jun-Nov) limits were removed.
- · Hardness monitoring was included.
- Footnotes were updated to reflect current DEQ guidance and changes in the reissued permit.

#### Part I.A.2. **Effluent Limitations and Monitoring Requirements:**

*Updates Part I.A.2. of the previous permit with the following:* 

- Changes were made to the format and introductory language.
- More stringent Copper limits were included.
- More stringent TRC limits were included.
- The E. coli monitoring was increased to 2/Week.
- Zinc limits were added.
- Cadmium limits were removed.
- Ammonia-N (Dec-May) limits were removed.
- Ammonia-N (Jun-Nov) limits were included.
- TKN (Jun-Nov) limits were removed.
- Hardness monitoring was included.
- Footnotes were updated to reflect current DEQ guidance and changes in the reissued permit.

#### Part I.A.3. Effluent Limitations and Monitoring Requirements:

*Updates Part I.A.3. of the previous permit with the following:* 

- Changes were made to the format and introductory language.
- More stringent TRC limits were included.
- The E. coli monitoring was increased to 2/Week.
- Cadmium limits were removed.
- Ammonia-N (Dec-May) limits were removed.
- Ammonia-N (Jun-Nov) limits were included.
- TKN (Jun-Nov) limits were removed.
- Hardness monitoring was included.
- Footnotes were updated to reflect current DEQ guidance and changes in the reissued permit.

# Part I.B. Additional TRC And E. coli Limitations and Monitoring Requirements: *Updates Part I.B. of the previous permit.* Required by Sewage Collection and Treatment (SCAT) Regulations and 9 VAC 25-260-170, Bacteria; other waters. Also, 40 CFR 122.41(e) requires the permittee, at all times, to properly operate and maintain all facilities and systems of treatment in order to comply with the permit. This ensures proper operation of chlorination equipment to maintain adequate disinfection.

- Part I.C. **Effluent Limitations and Monitoring Requirements Additional Instructions:** *Updates Part I.C. of the previous permit.* TP, Orthophosphate, and Nitrate-Nitrite were deleted. The paragraph regarding significant digits was revised. Authorized by VPDES Permit Regulation, 9 VAC 25-31-190.J.4 and 220.I. This condition is necessary when a maximum level of quantification and/or a specific analytical method is required in order to assess compliance with a permit limit or to compare effluent quality with a numeric criterion. The condition also establishes protocols for calculation of reported values. Nutrient reporting calculations were updated. §62.1 44.19:13 of the Code of Virginia defines how annual nutrient loads are to be calculated; this is carried forward in 9 VAC 25-820-70.
- Part I.D.1. **95% Capacity Reopener:** *Identical to Part I.D.1. of the previous permit.* Required by VPDES Permit Regulation, 9 VAC 25-31-200 B 4 for certain permits.
- Part I.D.2 **Indirect Dischargers:** *Identical to Part I.D.2. of the previous permit.* Required by VPDES Permit Regulation, 9 VAC 25-31-200 B 1 for all STPs that receive waste from someone other than the owner of the treatment works.
- Part I.D.3. **Materials Handling/Storage:** *Identical to Part I.D.3. of the previous permit.* 9 VAC 25-31-280.B.2. requires that the types and quantities of "wastes, fluids, or pollutants which are ... treated, stored, etc." be addressed for all permitted facilities.
- Part I.D.4. **O&M Manual Requirement:** *Updates Part I.D.4. of the previous permit.* Required by Code of Virginia 62.1-44.19, SCAT Regulations 9 VAC 25-790, and VPDES Permit Regulation 9 VAC 25-31-190 E for all STPs.
- Part I.D.5. **CTC/CTO Requirement:** *Identical to Part I.D.5. of the previous permit.* Required by Code of Virginia 62.1-44.19, SCAT Regulations 9 VAC 25-790, and VPDES Permit Regulation 9 VAC 25-31-190 E for all STPs.
- Part I.D.6. **SMP Requirement:** *Updates Part I.D.7. of the previous permit.* VPDES Permit Regulation 9 VAC 25-31-100 P, 220 B 2, and 420 through 720, and 40 CFR Part 503 require all treatment works treating domestic sewage to submit information on their sludge use and disposal practices and to meet specified standards for sludge use and disposal. Technical requirements are derived from the Virginia Pollution Abatement Permit Regulation (9 VAC 25-32-10 *et seq.*)
- Part I.D.7. **Licensed Operator Requirement:** *Identical to Part I.D.8. of the previous permit.* The VPDES Permit Regulation 9 VAC 25-31-200 C, the Code of Virginia 54.1-2300 et seq., and Rules and Regulations for Waterworks and Wastewater Works Operators 18 VAC 160-20-10 et seq., require licensure of operators.
- Part I.D.8. **Reliability Class:** *Updates Part I.D.9. of the previous permit.* Required by SCAT Regulations 9 VAC 25-790.
- Part I.D.9. **Water Quality Criteria Monitoring:** *Updates Part I.D.10. of the previous permit.* State Water Control Law at 62.1-44.21 authorizes the Board to request information needed to determine the discharge's impact on State waters. States are required to review data on discharges to identify actual or potential toxicity problems, or the attainment of water quality goals, according to 40 CFR Part 131, Water Quality Standards, subpart 131.11. To ensure that water quality criteria are maintained, the permittee is required to analyze the facility's effluent for the substances noted in Attachment A of this VPDES permit.
- Part I.D.10. **Treatment Works Closure Plan:** *Updates Part I.D.11. of the previous permit.* Required for all STPs per the State Water Control Law at 62.1-44.18.C. and 62.1-44.15:1.1., and the SCAT Regulations at 9 VAC 25-790-450.E. and 9 VAC 25-790-120.E.3.

#### Part I.D.11. **Reopeners**

- a. *Updates Part I.D.13. of the previous permit:* Section 303(d) of the Clean Water Act requires that total maximum daily loads (TMDLs) be developed for streams listed as impaired. This special condition is to allow the permit to be reopened if necessary to bring it into compliance with any applicable TMDL approved for the receiving stream. The reopener recognizes that, according to section 402(o)(1) of the Clean Water Act, limits and/or conditions may be either more or less stringent than those contained in this permit. Specifically, they can be relaxed if they are the result of a TMDL, basin plan, or other wasteload allocation prepared under section 303 of the Act.
- b. *New Requirement:* 9 VAC 25-40-70 A authorizes DEQ to include technology-based annual concentration limits in the permits of facilities that have installed nutrient control equipment, whether by new construction, expansion or upgrade.
- c. *Updates Part I.D.12. of the previous permit:* 9 VAC 25-31-390 A authorizes DEQ to modify VPDES permits to promulgate amended water quality standards.
- d. *Updates Part I.D.6. of the previous permit:* Required by the VPDES Permit Regulation, 9 VAC 25-31-220.C, for all permits issued to STPs.
- Part II **Conditions Applicable to All VPDES Permits:** *Identical to Part II of previous permit.* VPDES Permit Regulation 9 VAC 25-31-190 requires all VPDES permits to contain or specific ally cite the conditions listed